

VK507B45

CONNECTION TECHNOLOGY • CABLE SOCKETS / CONNECTORS PRE-ASSEMBLED ON ONE SIDE

, 5m, M9 Male (plug) 8pin Straight, Free conductor end, 8x0.14mm², PUR (Polyurethane), 125V, IP67, Shielded, Oil and cooling lubricants, Welding area



MECHANICAL FEATURES

Ambient temperature	-25 °C 70 °C
Cable infeed of A connection	Straight
Cable length	5 m
Degree of protection (IP)	IP67
Material of cable sheath	PUR (Polyurethane)
Number of cores	8
Version	Connection cable
Wire cross section	0.14 mm²

ELECTRICAL FEATURES

Flow resistance	3 mOhm
Number of pins of A connection	8
Rated current	1 A
Rated voltage	125 V
Shielded	+
Type of A electrical connection	M9
Type of B electrical connection	Free conductor end
Type of plug-in contact, A connection	Male (connector)
With LED display	-

OTHER FEATURES

Flame retardant	No
IR-networked	-
Oil and cooling lubricants	+
Welding area	+

Other

Packaging dimensions	200mm x 35.0mm x 300mm
Shipping weight	0.22kg
Tariff code	85444290




Classification

ipf product group	856
eClass 8.0	27279218
eClass 9.0	27060311
eClass 9.1	27060311
ETIM-5.0	EC001855
ETIM-6.0	EC001855
ETIM-7.0	EC001855

Connection

Dimensional drawing





Installation



Mounting / installation may only be carried out by a qualified electrician!

Disposal



Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Sensor Cables / Actuator Cables category:

Click to view products by IPF ELECTRONIC manufacturer:

Other Similar products are found below:

60963 60964 703000D02F2002 703000D02F300 703001D02F0602 703001D02F1201 703001D02F300 704000D02F120 773032K02F030
802027107404-1 802027213811-1 804001A09M150 805001A09M0502 84914-0235 84914-0237 885030A09M010 885030A09M020
8R4J30E03C3003 1200651332 1200651713 1200660844 1200660845 1200661173 1200680071 1200720053 1200720081 1200720099
1200720217 1200800231 1200860125 1200870123 1200980102 1200650218 1200650267 1200650298 1200660183 1200660782
1200660849 1200661295 1200661297 1200661342 1200661343 1200670080 1200670220 1200680331 1200720252 1200720255
1200720597 1200730184 1200860344