

H11G1, H11G2, H11G3
H11G1X



ISOCOM
COMPONENTS



HIGH VOLTAGE DARLINGTON OUTPUT OPTICALLY COUPLED ISOLATOR

APPROVALS

- UL recognised, File No. E91231
Package Code " JJ "

'X' SPECIFICATION APPROVALS

- H11G1X VDE 0884 in 3 available lead form :
 - STD
 - G form
 - SMD approved to CECC 00802

DESCRIPTION



The H11G_ series are optically coupled isolators consisting of an infrared light emitting diode and a high voltage NPN silicon photo darlington which has an integral base-emitter resistor to optimise switching speed and elevated temperature characteristics in a standard 6pin dual in line plastic package.

FEATURES

- Options :-
 - 10mm lead spread - add G after part no.
 - Surface mount - add SM after part no.
 - Tape&reel - add SMT&R after part no.
- High Isolation Voltage (5.3kV_{RMS}, 7.5kV_{PK})
- High Current Transfer Ratio (1000% min)
- High BV_{CEO} (H11G1 - 100V min.)
- Low collector dark current :-
100nA max. at 80V V_{CE}
- Low input current 1mA I_F

APPLICATIONS

- Modems
- Copiers, facsimiles
- Numerical control machines
- Signal transmission between systems of different potentials and impedances



ABSOLUTE MAXIMUM RATINGS (25°C unless otherwise specified)

| | |
|---|-----------------|
| Storage Temperature | -40°C to +125°C |
| Operating Temperature | -25°C to +100°C |
| Lead Soldering Temperature (1/16 inch (1.6mm) from case for 10 secs) | 260°C |

INPUT DIODE

| | |
|-------------------|------|
| Forward Current | 50mA |
| Reverse Voltage | 6V |
| Power Dissipation | 70mW |

OUTPUT TRANSISTOR

| | |
|--|------------|
| Collector-emitter Voltage BV _{CEO} H11G3,H11G2,H11G1 | 55,80,100V |
| Collector-base Voltage BV _{CBO} H11G3,H11G2,H11G1 | 55,80,100V |
| Emitter-base Voltage BV _{EBO} | 6V |
| Collector Current | 150mA |
| Power Dissipation | 300mW |

POWER DISSIPATION

| | |
|-------------------------|-------|
| Total Power Dissipation | 350mW |
|-------------------------|-------|

ISOCOM COMPONENTS LTD
Unit 25B, Park View Road West,
Park View Industrial Estate, Brenda Road
Hartlepool, TS25 1UD England Tel: (01429)863609
Fax: (01429) 863581 e-mail sales@isocom.co.uk



ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ Unless otherwise noted)

| PARAMETER | | MIN | TYP | MAX | UNITS | TEST CONDITION |
|-----------|---|--------------------|-------------------|-----|-----------------------|---|
| Input | Forward Voltage (V_F) | | 1.2 | 1.5 | V | $I_F = 10\text{mA}$ |
| | Reverse Current (I_R) | | | 10 | μA | $V_R = 4\text{V}$ |
| Output | Collector-emitter Breakdown (BV_{CEO}) H11G1 H11G2 H11G3 | 100 80 55 | | | V | $I_C = 1\text{mA}$ $I_C = 1\text{mA}$ $I_C = 1\text{mA}$ |
| | Collector-base Breakdown (BV_{CBO}) H11G1 H11G2 H11G3 | 100 80 55 | | | V | $I_C = 100\mu\text{A}$ $I_C = 100\mu\text{A}$ $I_C = 100\mu\text{A}$ |
| | Emitter-base Breakdown (BV_{EBO}) | 6 | | | V | $I_E = 0.1\text{mA}$ |
| | Collector-emitter Dark Current (I_{CEO}) H11G1 H11G2 H11G3 | | 100 | nA | | $V_{CE} = 80\text{V}$ $V_{CE} = 60\text{V}$ $V_{CE} = 30\text{V}$ |
| | Collector Output Current (I_C) H11G1,H11G2 H11G1,H11G2 H11G3 | 100 5 2 | | | mA | $10\text{mA} I_F, 1.2\text{V} V_{CE}$ $1\text{mA} I_F, 5\text{V} V_{CE}$ $1\text{mA} I_F, 5\text{V} V_{CE}$ |
| | Collector-emitter Saturation Voltage $V_{CE(SAT)}$ H11G1,H11G2 H11G1,H11G2 H11G3 | | 1.0 1.2 1.2 | | V | $1\text{mA} I_F, 1\text{mA} I_C$ $16\text{mA} I_F, 50\text{mA} I_C$ $20\text{mA} I_F, 50\text{mA} I_C$ |
| | Input to Output Isolation Voltage V_{ISO} | 5300 7500 | | | V_{RMS} V_{PK} | See note 1 See note 1 |
| | Input-output Isolation Resistance R_{ISO} | 5×10^{10} | 10 ¹¹ | | Ω | $V_{IO} = 500\text{V}$ (note 1) |
| | Input-output Capacitance C_f | | 0.6 | | pF | $V = 0, f = 1\text{MHz}$ |
| | Response time (Rise), t_r Response time (Fall), t_f | | 100 20 | | μs | $I_C = 20\text{mA}, V_{CE} = 2\text{V}$, $R_L = 100\Omega$ |


Note 1 Measured with input leads shorted together and output leads shorted together.

Note 2 Special Selections are available on request. Please consult the factory.


FIGURE 1




Collector Power Dissipation vs. Ambient Temperature




Normalized Output Current vs. Collector-emitter Voltage




Forward Current vs. Ambient Temperature




Normalized Output Current vs. Ambient Temperature



Normalized Output Current vs. Input Current



Collector Dark Current vs. Ambient Temperature



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [High Speed Optocouplers](#) category:

Click to view products by [Isocom manufacturer:](#)

Other Similar products are found below :

[6N136F](#) [PS8502L2-AX](#) [ACNW261L-000E](#) [ACPL-344JT-000E](#) [ACPL-K49T-500E](#) [ACPL-K75T-000E](#) [ACPL-W21L-560E](#) [ACPL-K44T-500E](#) [TLP187\(TPL,E\(T](#) [TLP2601\(TP1,F\)](#) [610737H](#) [6N137A-X001](#) [6N137A-X017T](#) [6N139-X007T](#) [HCPL2630M](#) [HCPL2731SM](#) [TLP555\(F\)](#) [HCPL2630SM](#) [PS2841-4A-F3-AX](#) [PS9817A-1-F3-AX](#) [PS9821-2-F3-AX](#) [ORPC-817D](#) [ORPC-817M/C](#) [ORPC-817M/B](#) [PT17-51C/L129\(BIN2\)](#) [TLP521-4GBSM](#) [UMW817C](#) [6N137S1\(TA\)](#) [TLP521GB](#) [TLP521GB-S](#) [PS2501](#) [PS2501-S](#) [TLP785GB](#) [TLP785GB-S](#) [LTV-214-G](#) [TLP2766A\(E](#) [TLP2766A\(LF4,E](#) [LCR-0202](#) [EL814S1\(TA\)-V](#) [PC817X4NSZ2B](#) [CYPC817](#) [OR-MOC3023](#) [TLP267J\(TPL,E\(T](#) [TLP109\(TPL,E\(O](#) [EL2514S1\(TU\)\(CLW\)-G](#) [EL816S2\(C\)\(TU\)-F](#) [EL814S\(A\)\(TU\)](#) [TLP281-4](#) [MOC3023M](#) [ACPL-K49T-060E](#)