

## Datasheet for part number DB-25P-1-A-5-N-A191-K87

Our Catalog Part Number: DB-25P-1-A-5-N-A191-K87

Our Global Manufacturing Part Number: 121073-3242 D

Brand: Cannon Product Category: D Sub Product Line: D Sub Series: ORIGINAL D

Product Datasheet	
General	Standard D-Subminiature
Wire Gauge Range AWG	AWG 20-28
Mating Cycles	200
Dielectric Withstanding Voltage	1200 VAC at sea level
Current Rating	7.5 A at 85°C / 5 A at 105°C
Contact Resistance	10 milli Ohm max
Operating Temperature	-55°/+125°
Salt Spray Test	20 hours
Shell Material	steel
Shell Finish	tin
Insulator Material	Thermoplastic, type PCT UL 94V-0
Insulator Color	black
Contact Arrangement	25 contacts size 20
Gender	Pin
Contact Type	turned
Contact Material	copper alloy
Contact Finish	gold over nickel (Performance Class 2)
Contact Termination	Right angled solder
Termination Direction	contact termination at short side of trapezoid (Standard)
Mounting Methode	Plastic bracket with 0,120" (3,05mm) Through Hole

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Standard Connectors category:

Click to view products by ITT manufacturer:

Other Similar products are found below:

56F711-015 012-9507-004 LV242999-142T12 015-0341-000 015-0372-005 015-0372-008 015-8755-001 020419-0104 012-0467-000 012-0515-000 012-9507-034 012-9507-114 020745-0008 609-25P M24308/2-23Z CT2-14S-2PCA34 CT2-18-11PCAU CT2-36-15SC CT6-14S-2SC CT6E14SA7SC CT6E22-14PC CT6E22-14PS CT6E22-22PS M83513/01-FC M85049/48-3-2F 6STD09PCM99B70X 6STD09SCM99B30X 6STD09SCM99B30X 6STD09SCM99B30X 6STD15PCT99S40X 6STD15SCM99B30X 6STD15SCT99S40X 6STF09PCM05B70X 7-135760-9 MC11E-10-6SN 747552-3 MD1-21PS MDM-15SCBRM7-F222 MDM96517-699 MDM96521-744 MDVB1-21SL1 MIK0-1-7SH003 MIKQ6-7SH076 MIKQ7-7PH077 MIKQ7-7PH11 MIKQ7-7PH32 MJSV-28SL61 MKJ4A1F14-55S 8-135760-3 8STD09PCM99B30X PG-KV/PV-16-GROM-SEALING