

## Datasheet for part number DBMD-25P-J-F225

Our Catalog Part Number: DBMD-25P-J-F225

Brand: Cannon Product Category: D Sub Product Line: D Sub Series: D\*M

Product Datasheet	
General	D*M High reliable D-Sub Connectors
Wire Gauge Range AWG	AWG 20-28
Mating Cycles	200
Contact Arrangement	25 contacts size 20
Dielectric Withstanding Voltage	1000 VAC at sea level
Current Rating	7.5 A max
Contact Resistance	7.5 milli Ohm max
Operating Temperature	-55°/+125°
Salt Spray Test	20 hours
Shell Material	Passivated stainless steel
Shell Finish	Stainless steel shell
Insulator Material	Thermoplastic, type PCT UL 94V-0
Insulator Color	black
Gender	Pin
Contact Type	Right angled PCB
Contact Material	copper alloy
Contact Finish	gold over nickel
Hardware	90° Metal Bracket, 4-40 Fastener and 4-40 Screwlock
Disclaimer	Our facility is not currently certified by the DLA and this product is not covered by the QPL/QML.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Standard Connectors category:

Click to view products by ITT manufacturer:

Other Similar products are found below:

56F706-005-LI 56F711-015 LV242999-142T12 015-0341-000 015-0349-000 015-0350-000 015-8544-011 015-8755-001 017041-0005 020419-0104 012-0467-000 012-9507-114 020745-0008 609-25P 609-9P M24308/2-23Z M24308/2-36Z CT0-24-10SC CT0E20-8PS CT0E22-14SC CT0F16S-1SC CT0FA22-1SS CT0P14S-5SXS CT0P22-14PS CT0TA16-11SXCA232 CT0U22-14PSA206F127 CT1E20-19SS CT1E20-22SCAU-G9 CT1F22-14PC-G9 CT1FC22-2PC CT1FC24-28SSAU CT1N22-22SS CT2-10SL-3SC CT2-14S-2PCA34 CT2-18-10PS-FMLB-D CT2-18-11PCAU CT2-18-1PSAUA34 CT2-22-19SC CT2-22-19SS-A206 CT2-24-2PS CT2-28-12SC CT2-28-12SC A232 CT2-28-12SSA232 CT6-10SL-3SC CT6-10SL-4SC CT6-16-12SC CT6-18-10PSA206 CT6-18-10PSA232 CT6-18-1