

Datasheet for part number DBMM-25S-M-A101

Our Catalog Part Number: DBMM-25S-M-A101

Brand: Cannon Product Category: D Sub Product Line: D Sub Series: D*M

Product Datasheet	
General	D*M High reliable D-Sub Connectors
Wire Gauge Range AWG	AWG 20-28
Mating Cycles	500
Contact Arrangement	25 contacts size 20
Dielectric Withstanding Voltage	1000 VAC at sea level
Current Rating	7.5 A max
Contact Resistance	7.5 milli Ohm max
Operating Temperature	-55°/+150°
Salt Spray Test	48 hours {96 Hrs for Stainless Steel}
Shell Material	Steel
Shell Finish	Yellow chromate over cadmium
Insulator Material	Thermoplastic, type PCT UL 94V-0
Insulator Color	black
Gender	Socket
Contact Type	Straight PCB
Contact Material	copper alloy
Contact Finish	50 microinch gold over 40 microinch nickel
Hardware	.120" (3,05mm) Through Hole
Disclaimer	Our facility is not currently certified by the DLA and this product is not covered by the QPL/QML.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub MIL Spec Connectors category:

Click to view products by ITT manufacturer:

Other Similar products are found below:

M85049/50-5F MDM-9SH006A 850-056-0812 1218697-4 D38999/26WJ61PC L/C 1484349-1 17D25HV 1996840-1 243082-15 1757682-1 17D-E51218-1 17SDA15S 1883533-1 1883886-1 1883889-1 192900-0377 M24308/8-347 M83513/03-E09C 443961-3 5-1218949-1 550-031NF1R6K 3-1236089-2 550E001NF1R3J0L 550T001NF1R6K0L 557T283NF5B08 DC121073157 443869-3 443869-4 443869-5 550S004NF1R1B0F03 557E283NF1A06 527-019NF0303R2K1F 5-446405-1 550-031NF1R2E 550E003M2R9J0F04 550E003M3R9J0F05 550E024M104R9J0 550E024NF102R3J0B 550E039NF1R3J1-02 550S003M3R9B0F05 550S004M4R7M0F04 550S004NF1R1B1F02 550S008M3F0K0F04 550S086M5R3J0L 550S100NF3F0E 550T001M2R7E0L 550T001NF1F0B1L 550T001NF1R1K0G 550T001NF1R3K0G 550T001NF1R4K0L