

Datasheet for part number DCM-21WA4P-K87

Our Catalog Part Number: DCM-21WA4P-K87

Our Global Manufacturing Part Number: 053514-1570

Brand: Cannon Product Category: D Sub Product Line: D Sub Series: COMBO D

Product Datasheet	
General	Combo D Series: D-Subminiature offering mixed layouts
Wire Gauge Range AWG	AWG 8-26
Mating Cycles	50
Contact Arrangement	21WA4 (17 contacts size 20, 4 empty size 8 cavities)
Dielectric Withstanding Voltage	500 VAC at sea level
Current Rating Signal Contacts	7.5 max
Contact Resistance	10 milli Ohm max
Operating Temperature	-55°/+125°
Salt Spray Test	20 hours
Shell Material	steel
Shell Finish	pure tin over nickel
Insulator Material	Thermoplastic, type PCT UL 94V-0
Insulator Color	black
Gender	Pin
Contact Type	Solder pot
Contact Material	copper alloy
Contact Finish	gold flash (Performance Class 3)
Mounting Method	.120" (3,05mm) Through Hole

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Mixed Contact Connectors category:

Click to view products by ITT manufacturer:

Other Similar products are found below:

790-025SF-5P5NMN 790-025SJ-7P7NML DAM-7W2PC L717TWB5W5P3R L717TWB5W5PRM84 L717TWP3W3P
3003W3PXX56N40X 3005W5PXX99E40X 3005W5SXX99A30X 3005W5SXX99E40X 3013W6SCM99A10X 3036W4PCM41A10X
3036W4SCM99A10X FCE17-E2W2SS-2N0 212522-7 PII-468-1 3003W3PXX43A10X 3003W3SXX56N40X 3005W5PXX88N40X
3008W8SXX57A30X 3009W4PCT57P20X 3017W2SAR69C40X 3024W7SCM99A10X 302W2CPXX56N40X 321WA4PXK99A60X
3F3SSC22S41A30X L717TWA7W2PP2SY3R DBM-17W2S-1A8N-A190-A197-1 421WA4PCR50E20X 09693009176 09693909015
6017W2PCM41B30X 790-061SH-36W2NMNA 790-044SE-7P3MNPB 790-043PE-11P2MPA 790-043PB-2P2MPB 790-029SB-2P2MEPA
790-028PK-9P9MPA 790-028PH-54P2MGA 790-028PH-36P2MNA 790-028PB-2P2MPA 790-027SH-5W5MTEP 790-026PH-54P2NUG
790-026PH-54P2MP 790-026PH-36P2ZNUG 790-026PH-36P2MG 790-026PD-3P3MP 790-025SJ-7P7EMS 790-025SH-36W2NMT 790-025SB-2P2EMS