

## Datasheet for part number DCMAM-37S-F225

	Our Catalog Part Number: DCMAM-37S-F225 Our Global Manufacturing Part Number: 112235-0041		
	Brand: Cannon Product Category: D Sub Product Line: D Sub Series: D*MA		

Product Datasheet	
General	D*M High reliable D-Sub Connectors with crimp termination
Wire Gauge Range AWG	Standard: AWG 20-28. High Density: AWG 22-28
Mating Cycles	500
Contact Arrangement	37 contacts size 20
Dielectric Withstanding Voltage	1000 VAC at sea level
Current Rating	7.5 A max
Contact Resistance	10 milli Ohm max
Operating Temperature	-55°/+150°
Salt Spray Test	48 hours {96 Hrs for Stainless Steel}
Shell Material	Passivated stainless steel
Shell Finish	Stainless steel shell
Insulator Material	Thermoplastic, type PCT UL 94V-0
Insulator Color	black
Gender	Socket
Contact Type	Crimp
Contact Material	copper alloy
Contact Finish	gold over nickel (Performance Class 2)
Hardware	.120" (3,05mm) Through Hole
Disclaimer	Our facility is not currently certified by the DLA and this product is not covered by the QPL/QML.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub High Density Connectors category:

Click to view products by ITT manufacturer:

Other Similar products are found below :

97-3250-11 163A17089X 164A17199X 164C18629X L717HDB44POL2R210 L717HDEH15POL2 L777HDE15P L77HDE15SC309 163A16759X 163A16839X 163A16989X 163A17079X 164A17329X 164A18219X 241A16440X 241A16550X 241A16680X 241A20810X 241A25740X CT25-44P MDBE15PE766 L177HDE15SOL2RM23 L177HRC62SVFM L177HRCG62S L717HDEG15POL2RM5 L77HDA26SVF L77HDE15SD1CO L77HDEH15SOL2RM832 DAMA-15S-WS 443895-3 106698-1 280-012K2C DBMV13H3SNA197 L177HRB44S 164A17039X 09562004701510 L777HRC62P 241A17960X 164A18269X 280-019S1S9MEN L777HDEG15P 280-018P3S25MEGN 206504-2 40-9415HDSP 40-9515HDSP 2057140-1 C115370-6002 DFMA104SNMBFR172FR022 HDC9F200E2S L717HDAG26POL2RM8