

Datasheet for part number DDA50P-K87-F0

Our Catalog Part Number: DDA-50P-K87-F0

Our Global Manufacturing Part Number: 119998-0354

Brand: Cannon Product Category: D Sub Product Line: D Sub Series: D*A

Product Datasheet	
General	Crimp Connector without contacts
Wire Gauge Range AWG	AWG 20-28
Mating Cycles	50, 200
Dielectric Withstanding Voltage	500 VAC at sea level
Current Rating	5 A max
Contact Resistance	15 milli Ohm max
Operating Temperature	-55°/+105°
Salt Spray Test	12 hours
Shell Material	steel
Shell Finish	tin
Insulator Material	Thermoplastic, type PCT UL 94V-0
Insulator Color	black
Contact Arrangement	50 contacts size 20
Gender	Pin
Contacts	delivery without contacts, please order separately
Available contacts Size 20 Male:	AWG 20-24: A191: 980-2002-305 / 400 per Reel Gold flash (class 3): 980-200-924 / 5000 per Reel A191 (class 2): 980-200-945 / 5000 per Reel
Contact Type	stamped
Contact Material	copper alloy
Contact Finish	gold over nickel
Contact Termination	Crimp
Mounting Methode	.120" (3,05mm) Through Hole

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for itt manufacturer:

Other Similar products are found below:

BKAF3-68102-25 MDM-9SL1B NEM-QTHSSB-68PGNS-B MJSR-34PL61 096520-0863 096520-0927 153205-3053 096522-0534 097391-0281 MDM-37PCBR-F222 CA3108E14S-5PBA176A232 MJSR-42PH003 MDM-51PCBRP-L56 CV3456L28-15P KPSE06F20-41SA206F0 CB2-18-3SCA232 MS3106E22-14P 252-7689-001 097414-0074 130680-0000 CT6E18-11SCA206 CA3101E10SL-4SF80DN MS3100F14S-7S CA3101E10SL-4PBA176F42 053513-4377 051212-0001 MS3101E181SW 980-8001-545 CAR3102A20-27SX 024251-0016-R 024253-0025 024265-0001 024270-0015 024271-0022 024273-0043 024288-0001 M24308/24-21F CT1F22-7SS CT2-20-23SWS CT2-20-23SXS CT2-36-10PCAU CT6-24-11PSA206 CT6F36-10PCA152 CT6F9767-14-4-14S-5PC CT6T9767-14-4-14SA7SS D38999/20FG16PA-LC - D38999/26JH21PB-LC MD1-21PS MDM-15PH001B-A174 MDM-15PH003B-A174