

## Datasheet for part number DE-9P-1-A-9-N-K87

Our Catalog Part Number: DE-9P-1-A-9-N-K87

Our Global Manufacturing Part Number: 121073-4875 D

Brand: Cannon Product Category: D Sub Product Line: D Sub Series: ORIGINAL D

Draduct Datashast	
Product Datasheet	
General	Standard D-Subminiature
Wire Gauge Range AWG	AWG 20-28
Mating Cycles	50
Dielectric Withstanding Voltage	1200 VAC at sea level
Current Rating	7.5 A at 85°C / 5 A at 105°C
Contact Resistance	10 milli Ohm max
Operating Temperature	-55°/+125°
Salt Spray Test	20 hours
Shell Material	steel
Shell Finish	tin
Insulator Material	Thermoplastic, type PCT UL 94V-0
Insulator Color	black
Contact Arrangement	9 contacts size 20
Gender	Pin
Contact Type	turned
Contact Material	copper alloy
Contact Finish	gold flash (Performance Class 3)
Contact Termination	Right angled solder
Termination Direction	contact termination at short side of trapezoid (Standard)
Mounting Methode	Metal bracket with M3 Captive Nut

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Standard Connectors category:

Click to view products by ITT manufacturer:

Other Similar products are found below:

56F706-005-LI 56F711-015 LV242999-142T12 015-0341-000 015-0349-000 015-0350-000 015-8544-011 015-8755-001 017041-0005 020419-0104 012-0467-000 012-9507-114 020745-0008 609-25P 609-9P M24308/2-23Z M24308/2-36Z CT0-24-10SC CT0E20-8PS CT0E22-14SC CT0F16S-1SC CT0FA22-1SS CT0P14S-5SXS CT0P22-14PS CT0TA16-11SXCA232 CT0U22-14PSA206F127 CT1E20-19SS CT1E20-22SCAU-G9 CT1F22-14PC-G9 CT1FC22-2PC CT1FC24-28SSAU CT1N22-22SS CT2-10SL-3SC CT2-14S-2PCA34 CT2-18-10PS-FMLB-D CT2-18-11PCAU CT2-18-1PSAUA34 CT2-22-19SC CT2-22-19SS-A206 CT2-24-2PS CT2-28-12SC CT2-28-12SC A232 CT2-28-12SSA232 CT6-10SL-3SC CT6-10SL-4SC CT6-16-12SC CT6-18-10PSA206 CT6-18-10PSA232 CT6-18-1