

## Datasheet for part number DE-9P-0L2-K87

Our Catalog Part Number: DE-9P-0L2-K87

Our Global Manufacturing Part Number: 121073-2250 D

Brand: Cannon Product Category: D Sub Product Line: D Sub Series: ORIGINAL D

Product Datasheet	
General	Standard D-Subminiature
Wire Gauge Range AWG	AWG 20-28
Mating Cycles	50
Dielectric Withstanding Voltage	1200 VAC at sea level
Current Rating	7.5 A at 85°C / 5 A at 105°C
Contact Resistance	10 milli Ohm max
Operating Temperature	-55°/+125°
Salt Spray Test	20 hours
Shell Material	steel
Shell Finish	tin
Insulator Material	Thermoplastic, type PCT UL 94V-0
Insulator Color	black
Contact Arrangement	9 contacts size 20
Gender	Pin
Contact Type	turned
Contact Material	copper alloy
Contact Finish	gold flash (Performance Class 3)
Contact Termination	Straight solder
Mounting Methode	.120" (3,05mm) Through Hole

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Standard Connectors category:

Click to view products by ITT manufacturer:

Other Similar products are found below:

56F711-015 012-9507-004 LV242999-142T12 015-0341-000 015-0349-000 015-0372-005 015-0372-008 015-8755-001 020419-0104 012-0467-000 012-0515-000 012-9507-034 012-9507-114 020745-0008 609-25P M24308315F CT2-14S-2PCA34 CT2-18-11PCAU CT2-36-15SC CT6-14S-2SC CT6E14SA7SC CT6E22-14PC CT6E22-14PS CT6E22-22PS M83513/01-FC M85049/48-3-2F 6STD09PCM99B70X 6STD09SCM99B30X 6STD09SCT99S40X 6STD15PCT99S40X 6STD15SCM99B30X 6STD15SCT99S40X 6STF09PCM05B70X 7-135760-9 MC11E-10-6SN 747552-3 MD1-21PS MDM-15SCBRM7-F222 MDM96517-699 MDM96521-744 MDVB1-21SL1 MIK0-1-7SH003 MIKQ6-7SH076 MIKQ7-7PH077 MIKQ7-7PH11 MIKQ7-7PH32 MIKQ9-7PH003 MJSV-28SL61 MKJ4A1F14-55S 8-135760-3