

## Datasheet for part number DEMM-9P-L-A101

Our Catalog Part Number: DEMM-9P-L-A101

Our Global Manufacturing Part Number: 051528-0081

Brand: Cannon Product Category: D Sub Product Line: D Sub Series: D\*M

Product Datasheet	
General	D*M High reliable D-Sub Connectors
Wire Gauge Range AWG	AWG 20-28
Mating Cycles	500
Contact Arrangement	9 contacts size 20
Dielectric Withstanding Voltage	1000 VAC at sea level
Current Rating	7.5 A max
Contact Resistance	7.5 milli Ohm max
Operating Temperature	-55°/+150°
Salt Spray Test	48 hours {96 Hrs for Stainless Steel}
Shell Material	Steel
Shell Finish	Yellow chromate over cadmium
Insulator Material	Thermoplastic, type PCT UL 94V-0
Insulator Color	black
Gender	Pin
Contact Type	Right angle solder
Contact Material	copper alloy
Contact Finish	50 microinch gold over 40 microinch nickel
Hardware	.120" (3,05mm) Through Hole
Disclaimer	Our facility is not currently certified by the DLA and this product is not covered by the QPL/QML.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub MIL Spec Connectors category:

Click to view products by ITT manufacturer:

Other Similar products are found below:

M24308/4-13Z M8351307-B D38999/20FJ43HN D38999/24WG11PB-LC D38999/24WG41HN MDM-15PH041P MDM-21PH041P MDM-21SH003B-K139 850-056-0812 1218697-4 DBMM25S MS27467T21F41S 17D25HV 1996840-1 243082-15 1663962-1 1757682-1 17D-E51218-1 17SDA15S 1883533-1 1883886-1 1883889-1 192900-0377 308-CP6P0441-024H M24308/2-3Z M24308/4-3Z M24308/4-4F M24308/4-4Z M24308/8-347 M83513/03-E09C M83723/75W2212N L/C D38999/24FJ29PN-LC D38999/24WG11SB-LC MDM-21PH046P 5-1218949-1 550-031NF1R6K 550E001NF1R3J0L 550T001NF1R6K0L 557T283NF5B08 C115368-1612B C115370-1717B DC121073157 443869-3 443869-4 443869-5 550S004NF1R1B0F03 550-031NF1R2E 550E003M2R9J0F04 550E003M3R9J0F05 550E024M104R9J0