

## Datasheet for part number M83513/02-GC

Our Catalog Part Number: M83513/02-GC

Our Global Manufacturing Part Number: 154181-0000

Brand: Cannon Product Category: Micro Product Line: Micros Series: M83513-1-4

Product Datasheet	
Series	Micro D Metal Shell - 0.050 inch spacing
Slash Sheet	Receptacle, Connector
Arrangement	51 Contact
Contact Typ	Solder pot
Contact Material	gold plated copper alloy
Contact Resistance	8 milliohms max.
Shell Material	Aluminum
Shell Finish	Cadmium / Yellow chromate over nickel
Insulator	LCP
Current Rating	3 A max.
Dielectric Withstanding Voltage	600 VAC at sea level 150 VAC at 70,00' altitude
Insulator Resistance	5000 megohms min.
Thermal Shock	-55°/+125°
Physical Shock	50 G's, 3 axes, 6 milisecond duration sawtooth pulse
Vibration	20G's, 10-2000 Hz. 12 hours
Durability	500 cycles of mating and unmating, 500 CPH max.
Moisture Resistance	Insulator resistance > 100 megohms
SaltSpray	48 hours

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub MIL Spec Connectors category:

Click to view products by ITT manufacturer:

Other Similar products are found below:

M85049/50-5F MDM-15PH006M7-A174 MDM-15SH001M7-A174 MDM-15SH003M7-A174 MDM-15SH006M7-A174 MDM-21PH046F MDM-21SH006B-A174 MDM-21SH006P-A174 MDM-21SH011P MDM-21SH011P-A174 MDM-21SH034B-A174 MDM25SL61P 850-056-0812 1218697-4 DA-59-20 1484349-1 17D25HV 1996840-1 243082-15 308-CP3C1001-076 1757682-1 17D-E51218-1 17SDA15S 1883889-1 192900-0377 308-CP6P0441-024H M83513/03-E09C 443961-3 MDM-15PH001F MDM-15PH001P-A174 MDM-15PH011P MDM-15PH011P-A174 MDM-15SH011F-A174 MDM-15SH011F-A174 MDM-15SH011P-A174 MDM-21PH041F MDM-21PH048F MDM-21SH003K-F222 MDM-21SH046B-A174 MDM-25PH001M7-A174 MDM-25SH011P MDM-9SH001F MDM-9SH006P-A174 5-1218949-1 550-031NF1R6K 3-1236089-2 550E001NF1R3J0L