

Datasheet for part number M83513/04-H14N

Our Catalog Part Number: M83513/04-H14N		
Our Global Manufacturing Part Number: 154183-0069 MS		
Brand: Cannon	Product Category: Micro Product Line: Micros Series: M83513-1-4	

Product Datasheet	
Series	Micro D Metal Shell - 0.050 inch spacing
Slash Sheet	Receptacle, Connector
Arrangement	100 Contact
Contact Typ	Crimp
Contact Material	gold plated copper alloy
Contact Resistance	8 milliohms max.
Wire Length	72 inch long, #26AWG per MIL-W-22759/11-26 Color Coded per MIL-STD-681, System 1, 10 colors repeating
Shell Material	Aluminum
Shell Finish	Electroless Nickel
Insulator	LCP
Current Rating	3 A max.
Dielectric Withstanding Voltage	600 VAC at sea level 150 VAC at 70,00' altitude
Insulator Resistance	5000 megohms min.
Thermal Shock	-55°/+125°
Physical Shock	50 G's, 3 axes, 6 milisecond duration sawtooth pulse
Vibration	20G's, 10-2000 Hz. 12 hours
Durability	500 cycles of mating and unmating, 500 CPH max.
Moisture Resistance	Insulator resistance > 100 megohms
SaltSpray	48 hours

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub MIL Spec Connectors category:

Click to view products by ITT manufacturer:

Other Similar products are found below :

M85049/50-5F MDM-21PH046F 850-056-0812 1218697-4 1484349-1 17D25HV 1996840-1 243082-15 1757682-1 17D-E51218-1 17SDA15S 1883533-1 1883886-1 1883889-1 192900-0377 M24308/8-347 M83513/03-E09C 443961-3 MDM-21PH041F MDM-21PH048F 5-1218949-1 550-031NF1R6K 3-1236089-2 550E001NF1R3J0L 550T001NF1R6K0L 557T283NF5B08 DB121073-56 DC121073157 443869-3 443869-4 443869-5 550S004NF1R1B0F03 557E283NF1A06 527-019NF0303R2K1F 5-446405-1 550-031NF1R2E 550E003M2R9J0F04 550E003M3R9J0F05 550E024M104R9J0 550E024NF102R3J0B 550E039NF1R3J1-02 550S003M3R9B0F05 550S004M4R7M0F04 550S004NF1R1B1F02 550S008M3F0K0F04 550S086M5R3J0L 550S100NF3F0E 550T001M2R7E0L 550T001NF1F0B1L 550T001NF1R1K0G