

## Datasheet for part number MDB1-51SCBRM7L56

Our Catalog Part Number: MDB1-51SCBRM7L56				
Our Global Manufacturing Part Number: 095489-0146				
Brand: Cannon	Product Category: Micro	Product Line: Micros	Series: MICRO	

Product Datasheet		
Series	Micro D Plastic Shell - 0.050 inch spacing	
Arrangement	51 Contact	
Gender	Socket	
Contact Material	gold plated copper alloy	
Contact Typ	crimp	
Contact Resistance	8 milliohms max.	
Termination Type	Condensed Right Angle PCB Terminations	
Termination	0.15" Min, #25AWG	
Shell Material	Glass-filled thermoset plastic	
Insulator Material	Diallyl phthalate with mounting holes	
Hardware	Jackpost, M83513/5-07 - Style	
PCB Hardware	no PCB mounting hardware	
Coupling	Jackscrew Coupling	
Current Rating	3 A max.	
Dielectric Withstanding Voltage	600 VAC at sea level 150 VAC at 70,00' altitude	
Insulator Resistance	5000 megohms min.	
Thermal Shock	-55°/+125°	
Physical Shock	50 G's, 3 axes, 6 milisecond duration sawtooth pulse	
Vibration	20G's, 10-2000 Hz. 12 hours	
Durability	500 cycles of mating and unmating, 500 CPH max.	
Moisture Resistance	Insulator resistance > 100 megohms	
SaltSpray	48 hours	
Disclaimer	Our facility is not currently certified by the DLA and this product is not covered by the QPL/QML.	

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Standard Connectors category:

Click to view products by ITT manufacturer:

Other Similar products are found below :

DCM37S732N DAM15P500 DEV09S364GTLF DEM09P032N DDM50P732N DAM15S332N 173109-2218 173109-2466 173109-2436 173109-2435 56F706-005-LI 56F711-015 015-0341-000 015-0372-008 015-8544-011 017041-0005 020419-0104 012-0515-000 012-9507-034 012-9507-114 012-9534-001 020745-0008 609-25P M24308/2-23Z M243082310F M243082410F M243082411F M24308/4-21 CT1A18-11PSA206 CT1N36-5SC CT2-16S-17PS CT2-20-15PCAU CT2-24-12PS CT2-24-28PSF127A206 CT2-32-9PC CT6F9767-14-4-14S-5PC CT6FA10SL-4PS CT7-18-10SC CT7-18-10SCAU CT7-18-12SCAU CT7-18-1PC CT7-18-1PCAU CT7-18-21SCAU M83513/01-FC M83723/76W24619 L/C M85049/48-3-2F 69001-865 6STD09PCM99B70X 6STD09SCM99B30X 6STD09SCT99S40X