



| $BV_{DSX}/$ BV_{DGX} | $R_{DS(on)}$ (max) | I_{DSS} (min) | Package |
|---------------------------|-----------------------|-----------------|---------|
| 250V | 2.5Ω | 400mA | SOT-223 |


Features

- High Breakdown Voltage: 250V
- On-Resistance: 2.5Ω max. at 25°C
- Low $V_{GS(off)}$ Voltage: -1.4 to -3.1V
- High Input Impedance
- Small Package Size: SOT-223

Applications

- Current Regulator
- Normally-On Switches
- Solid State Relays
- Converters
- Telecommunications
- Power Supply

Package Pinout



Description

The CPC3902 is a 250V, N-channel, depletion-mode, metal oxide semiconductor field effect transistor (MOSFET) built upon a proprietary third generation vertical DMOS process that realizes world-class, high voltage performance in an economical silicon gate process. This vertical DMOS process yields a robust device with high input impedance for power applications.

As with all MOS devices, the FET structure prevents thermal runaway and thermal-induced secondary breakdown, which makes the CPC3902 ideal for use in high-power applications.


The CPC3902 is a highly reliable FET device that has been used extensively in IXYS Integrated Circuits Division's Solid State Relays for industrial and telecommunications applications.

The CPC3902 is available in the SOT-223 package.

Ordering Information

| Part # | Description |
|------------|------------------------------------|
| CPC3902ZTR | SOT-223: Tape and Reel (1000/Reel) |

Circuit Symbol



Absolute Maximum Ratings @ 25°C

| Parameter | Ratings | Units |
|--|-------------|-------|
| Drain-to-Source Voltage | 250 | V |
| Gate-to-Source Voltage | ±15 | V |
| Pulsed Drain Current | 400 | mA |
| Total Package Dissipation ¹ | 1.8 | W |
| Operational Temperature | -55 to +110 | °C |
| Junction Temperature, Maximum | +125 | °C |
| Storage Temperature | -55 to +125 | °C |

¹ Mounted on 1"x1" 2 oz. Copper FR4 board.

Absolute Maximum Ratings are stress ratings. Stresses in excess of these ratings can cause permanent damage to the device. Functional operation of the device at conditions beyond those indicated in the operational sections of this data sheet is not implied.

Typical values are characteristic of the device at +25°C, and are the result of engineering evaluations. They are provided for information purposes only, and are not part of the manufacturing testing requirements.

Thermal Characteristics


| Device | Parameter | Symbol | Rating | Units |
|--------------------|---------------------|---------------|--------|-------|
| CPC3902Z (SOT-223) | Junction to Case | θ_{JC} | 14 | °C/W |
| | Junction to Ambient | θ_{JA} | 55 | |

Electrical Characteristics @ 25°C (Unless Otherwise Noted)


| Parameter | Symbol | Conditions | Min | Typ | Max | Units |
|--|-------------------|--|------|------|------|----------|
| Drain-to-Source Breakdown Voltage | BV_{DSX} | $V_{GS} = -5.5V, I_D = 100\mu A$ | 250 | - | - | V |
| Gate-to-Source Off Voltage | $V_{GS(off)}$ | $V_{DS} = 15V, I_D = 1\mu A$ | -1.4 | - | -3.1 | V |
| Change in $V_{GS(off)}$ with Temperature | $dV_{GS(off)}/dT$ | $V_{DS} = 15V, I_D = 1\mu A$ | - | - | 4.5 | mV/°C |
| Gate Body Leakage Current | I_{GSS} | $V_{GS} = \pm 15V, V_{DS} = 0V$ | - | - | 100 | nA |
| Drain-to-Source Leakage Current | $I_{D(off)}$ | $V_{GS} = -5.5V, V_{DS} = 250V$ | - | - | 1 | μA |
| Saturated Drain-to-Source Current | I_{DSS} | $V_{GS} = 0V, V_{DS} = 15V$ | 400 | - | - | mA |
| Static Drain-to-Source On-State Resistance | $R_{DS(on)}$ | $V_{GS} = 0V, I_D = 300mA, V_{DS} = 10V$ | - | - | 2.5 | Ω |
| Change in $R_{DS(on)}$ with Temperature | $dR_{DS(on)}/dT$ | | - | - | 2.5 | %/°C |
| Forward Transconductance | G_{fs} | $I_D = 200mA, V_{DS} = 10V$ | 400 | - | - | mmho |
| Input Capacitance | C_{ISS} | $V_{GS} = -3.5V$ $V_{DS} = 20V$ $f = 1MHz$ | - | 230 | - | pF |
| Common Source Output Capacitance | C_{OSS} | | - | 16 | - | |
| Reverse Transfer Capacitance | C_{RSS} | | - | 9.5 | - | |
| Source-Drain Diode Voltage Drop | V_{SD} | $V_{GS} = -5V, I_{SD} = 150mA$ | - | 0.72 | 1 | V |

PERFORMANCE DATA*


Instantaneous Transfer Characteristics
($V_{DS}=10V$)




Threshold Voltage
($I_{DS}=1\mu A$)




Transconductance vs. Drain Current
($V_{DS}=10V$)




Forward Safe Operating Bias
($V_{GS}=0V$, DC Load)




Output Characteristics




On-Resistance vs. Temperature
($V_{GS}=0V$, $I_D=300mA$)




Capacitance vs. Drain-Source Voltage
($V_{GS}=-3.5V$)




On-Resistance vs. Drain Current
($V_{GS}=0V$)



Blocking Voltage
($V_{GS}=-5V$, $I_L=10\mu A$)



Leakage Current vs. Temperature
($V_{GS}=-5V$, $V_{DS}=250V$)



*Unless otherwise noted, data presented in these graphs is typical of device operation at 25 $^\circ\text{C}$. For guaranteed parameters not indicated in the written specifications, please contact our application department.

Manufacturing Information

Moisture Sensitivity



All plastic encapsulated semiconductor packages are susceptible to moisture ingress. IXYS Integrated Circuits classifies its plastic encapsulated devices for moisture sensitivity according to the latest version of the joint industry standard, **IPC/JEDEC J-STD-020**, in force at the time of product evaluation. We test all of our products to the maximum conditions set forth in the standard, and guarantee proper operation of our devices when handled according to the limitations and information in that standard as well as to any limitations set forth in the information or standards referenced below.

Failure to adhere to the warnings or limitations as established by the listed specifications could result in reduced product performance, reduction of operable life, and/or reduction of overall reliability.

This product carries a **Moisture Sensitivity Level (MSL)** classification as shown below, and should be handled according to the requirements of the latest version of the joint industry standard **IPC/JEDEC J-STD-033**.

| Device | Moisture Sensitivity Level (MSL) Rating |
|----------|---|
| CPC3902Z | MSL 1 |

ESD Sensitivity



This product is **ESD Sensitive**, and should be handled according to the industry standard **JESD-625**.

Soldering Profile

Provided in the table below is the **IPC/JEDEC J-STD-020** Classification Temperature (T_c) and the maximum dwell time the body temperature of these surface mount devices may be ($T_c - 5$)°C or greater. The Classification Temperature sets the Maximum Body Temperature allowed for these devices during reflow soldering processes.

| Device | Classification Temperature (T_c) | Dwell Time (t_p) | Max Reflow Cycles |
|----------|--------------------------------------|----------------------|-------------------|
| CPC3902Z | 260°C | 30 seconds | 3 |


Board Wash

IXYS Integrated Circuits recommends the use of no-clean flux formulations. Board washing to reduce or remove flux residue following the solder reflow process is acceptable provided proper precautions are taken to prevent damage to the device. These precautions include but are not limited to: using a low pressure wash and providing a follow up bake cycle sufficient to remove any moisture trapped within the device due to the washing process. Due to the variability of the wash parameters used to clean the board, determination of the bake temperature and duration necessary to remove the moisture trapped within the package is the responsibility of the user (assembler). Cleaning or drying methods that employ ultrasonic energy may damage the device and should not be used. Additionally, the device must not be exposed to halide flux or solvents.




Mechanical Dimensions

CPC3902Z



CPC3902ZTR Tape & Reel



For additional information please visit our website at: www.ixysic.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [MOSFET](#) category:

Click to view products by [IXYS](#) manufacturer:

Other Similar products are found below :

[614233C](#) [648584F](#) [IRFD120](#) [JANTX2N5237](#) [FCA20N60_F109](#) [FDZ595PZ](#) [2SK2545\(Q,T\)](#) [405094E](#) [423220D](#) [TPCC8103,L1Q\(CM](#)
[MIC4420CM-TR](#) [VN1206L](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [SSM6J414TU,LF\(T](#) [751625C](#) [BUK954R8-60E](#) [NTE6400](#) [SQJ402EP-](#)
[T1-GE3](#) [2SK2614\(TE16L1,Q\)](#) [2N7002KW-FAI](#) [DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [ECH8691-TL-W](#) [FCAB21350L1](#) [P85W28HP2F-](#)
[7071](#) [DMN1053UCP4-7](#) [NTE221](#) [NTE222](#) [NTE2384](#) [NTE2903](#) [NTE2941](#) [NTE2945](#) [NTE2946](#) [NTE2960](#) [NTE2967](#) [NTE2969](#) [NTE2976](#)
[NTE6400A](#) [NTE2910](#) [NTE2916](#) [NTE2956](#) [NTE2911](#) [DMN2080UCB4-7](#) [TK10A80W,S4X\(S](#) [SSM6P69NU,LF](#) [DMP22D4UFO-7B](#)
[DMN1006UCA6-7](#) [DMN16M9UCA6-7](#)