


**Polar™ HiPerFET™  
Power MOSFET**


**IXFB100N50P**

**$V_{DSS}$**  = **500V**  
 **$I_{D25}$**  = **100A**  
 **$R_{DS(on)}$**  ≤ **49mΩ**  
 **$t_{rr}$**  ≤ **200ns**

N-Channel Enhancement Mode  
Avalanche Rated  
Fast Intrinsic Rectifier



**PLUS264™**



G = Gate      D = Drain  
S = Source      Tab = Drain

Symbol	Test Conditions	Maximum Ratings	
$V_{DSS}$	$T_J = 25^\circ\text{C}$ to $150^\circ\text{C}$	500	V
$V_{DGR}$	$T_J = 25^\circ\text{C}$ to $150^\circ\text{C}$ , $R_{GS} = 1\text{M}\Omega$	500	V
$V_{GSS}$	Continuous	±30	V
$V_{GSM}$	Transient	±40	V
$I_{D25}$	$T_C = 25^\circ\text{C}$	100	A
$I_{DM}$	$T_C = 25^\circ\text{C}$ , Pulse Width Limited by $T_{JM}$	250	A
$I_A$	$T_C = 25^\circ\text{C}$	100	A
$E_{AS}$	$T_C = 25^\circ\text{C}$	5	J
$dv/dt$	$I_S \leq I_{DM}$ , $V_{DD} \leq V_{DSS}$ , $T_J \leq 150^\circ\text{C}$	20	V/ns
$P_D$	$T_C = 25^\circ\text{C}$	1890	W
$T_J$		-55 ... +150	°C
$T_{JM}$		150	°C
$T_{stg}$		-55 ... +150	°C
$T_L$	Maximum Lead Temperature for Soldering	300	°C
$T_{SOLD}$	Plastic Body for 10s	260	°C
$F_c$	Mounting Force	30..120/6.7..27	N/lb
<b>Weight</b>		10	g

### Features

- Avalanche Rated
- Low Package Inductance
- Fast Intrinsic Rectifier
- Low  $R_{DS(on)}$  and  $Q_G$

### Advantages

- Easy to Mount
- Space Savings

### Applications

- DC-DC Converters
- Battery Chargers
- Switch-Mode and Resonant-Mode Power Supplies
- Uninterrupted Power Supplies
- AC Motor Drives
- High Speed Power Switching Applications

Symbol	Test Conditions ( $T_J = 25^\circ\text{C}$ Unless Otherwise Specified)	Characteristic Values		
		Min.	Typ.	Max.
$BV_{DSS}$	$V_{GS} = 0\text{V}$ , $I_D = 3\text{mA}$	500		V
$V_{GS(th)}$	$V_{DS} = V_{GS}$ , $I_D = 8\text{mA}$	3.0		V
$I_{GSS}$	$V_{GS} = \pm 30\text{V}$ , $V_{DS} = 0\text{V}$			$\pm 200 \text{ nA}$
$I_{DSS}$	$V_{DS} = V_{DSS}$ , $V_{GS} = 0\text{V}$ $T_J = 125^\circ\text{C}$			$25 \mu\text{A}$ 2 mA
$R_{DS(on)}$	$V_{GS} = 10\text{V}$ , $I_D = 0.5 \cdot I_{DSS}$ , Note 1			49 mΩ


Symbol	Test Conditions (T <sub>J</sub> = 25°C Unless Otherwise Specified)	Characteristic Values		
		Min.	Typ.	Max.
<b>g<sub>fs</sub></b>	V <sub>DS</sub> = 20V, I <sub>D</sub> = 50A, Note 1	50	80	S
<b>C<sub>iss</sub></b>		20		nF
<b>C<sub>oss</sub></b>		1700		pF
<b>C<sub>rss</sub></b>		140		pF
<b>t<sub>d(on)</sub></b>	<b>Resistive Switching Times</b> V <sub>GS</sub> = 10V, V <sub>DS</sub> = 0.5 • V <sub>DSS</sub> , I <sub>D</sub> = 0.5 • I <sub>DSS</sub> R <sub>G</sub> = 1Ω (External)	36		ns
<b>t<sub>r</sub></b>		29		ns
<b>t<sub>d(off)</sub></b>		110		ns
<b>t<sub>f</sub></b>		26		ns
<b>Q<sub>g(on)</sub></b>		240		nC
<b>Q<sub>gs</sub></b>		96		nC
<b>Q<sub>gd</sub></b>		78		nC
<b>R<sub>thJC</sub></b>			0.066 °C/W	
<b>R<sub>thCS</sub></b>		0.13		°C/W

### Source-Drain Diode







Symbol	Test Conditions (T <sub>J</sub> = 25°C Unless Otherwise Specified)	Characteristic Values		
		Min.	Typ.	Max.
<b>I<sub>s</sub></b>	V <sub>GS</sub> = 0V		100	A
<b>I<sub>SM</sub></b>	Repetitive, Pulse Width Limited by T <sub>JM</sub>		250	A
<b>V<sub>SD</sub></b>	I <sub>F</sub> = 100A, V <sub>GS</sub> = 0V, Note 1		1.5	V
<b>t<sub>rr</sub></b>	I <sub>F</sub> = 25A, -di/dt = 100A/μs V <sub>R</sub> = 100V, V <sub>GS</sub> = 0V	0.6	250	ns
<b>Q<sub>RM</sub></b>			6.0	μC
<b>I<sub>RM</sub></b>				A







Note 1. Pulse test, t ≤ 300μs, duty cycle, d ≤ 2%.



PLUS264™ (IXFB) Outline



SYM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	.185	.209	4.70	5.31
A1	.102	.118	2.59	3.00
b	.037	.055	0.94	1.40
b1	.087	.102	2.21	2.59
b2	.110	.126	2.79	3.20
c	.017	.029	0.43	0.74
D	1.007	1.047	25.58	26.59
E	.760	.799	19.30	20.29
e	.215 BSC		5.46 BSC	
L	.779	.842	19.79	21.39
L1	.087	.102	2.21	2.59
Q	.240	.256	6.10	6.50
Q1	.330	.346	8.38	8.79
ØR	.155	.187	3.94	4.75
ØR1	.085	.093	2.16	2.36

**Fig. 1. Output Characteristics @  $T_J = 25^\circ\text{C}$** **Fig. 2. Extended Output Characteristics @  $T_J = 25^\circ\text{C}$** **Fig. 3. Output Characteristics @  $T_J = 125^\circ\text{C}$** **Fig. 4.  $R_{DS(on)}$  Normalized to  $I_D = 50\text{A}$  Value vs. Junction Temperature****Fig. 5.  $R_{DS(on)}$  Normalized to  $I_D = 50\text{A}$  Value vs. Drain Current****Fig. 6. Maximum Drain Current vs. Case Temperature**

**Fig. 7. Input Admittance****Fig. 8. Transconductance****Fig. 9. Forward Voltage Drop of Intrinsic Diode****Fig. 10. Gate Charge****Fig. 11. Capacitance****Fig. 12. Forward-Bias Safe Operating Area**

**Fig. 13. Maximum Transient Thermal Impedance****Fig. 14. Cauer Thermal Network**

i	$R_i (\text{ }^{\circ}\text{C}/\text{W})$	$C_i (\text{J}/{}^{\circ}\text{C})$
1	0.0011707	0.0031990
2	0.0252980	0.0449880
3	0.0280620	0.7284100
4	0.0091690	



---

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [MOSFET](#) category:*

*Click to view products by [IXYS](#) manufacturer:*

Other Similar products are found below :

[614233C](#) [648584F](#) [IRFD120](#) [JANTX2N5237](#) [FCA20N60\\_F109](#) [FDZ595PZ](#) [2SK2545\(Q,T\)](#) [405094E](#) [423220D](#) [TPCC8103,L1Q\(CM](#)  
[MIC4420CM-TR](#) [VN1206L](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [SSM6J414TU,LF\(T](#) [751625C](#) [BUK954R8-60E](#) [NTE6400](#) [SQJ402EP-](#)  
[T1-GE3](#) [2SK2614\(TE16L1,Q\)](#) [2N7002KW-FAI](#) [DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [ECH8691-TL-W](#) [FCAB21350L1](#) [P85W28HP2F-](#)  
[7071](#) [DMN1053UCP4-7](#) [NTE221](#) [NTE222](#) [NTE2384](#) [NTE2903](#) [NTE2941](#) [NTE2945](#) [NTE2946](#) [NTE2960](#) [NTE2967](#) [NTE2969](#) [NTE2976](#)  
[NTE6400A](#) [NTE2910](#) [NTE2916](#) [NTE2956](#) [NTE2911](#) [DMN2080UCB4-7](#) [TK10A80W,S4X\(S](#) [SSM6P69NU,LF](#) [DMP22D4UFO-7B](#)  
[DMN1006UCA6-7](#) [DMN16M9UCA6-7](#)