


**High Voltage IGBT  
For Capacitor Discharge  
Applications**

(Electrically Isolated Tab)


**IXGF25N300**



$V_{CES}$  = 3000V  
 $I_{C25}$  = 27A  
 $V_{CE(sat)}$  ≤ 3.0V

Symbol	Test Conditions	Maximum Ratings	
$V_{CES}$	$T_J = 25^\circ\text{C}$ to $150^\circ\text{C}$	3000	V
$V_{CGR}$	$T_J = 25^\circ\text{C}$ to $150^\circ\text{C}$ , $R_{GE} = 1\text{M}\Omega$	3000	V
$V_{GES}$	Continuous	± 20	V
$V_{GEM}$	Transient	± 30	V
$I_{C25}$	$T_C = 25^\circ\text{C}$	27	A
$I_{C90}$	$T_C = 90^\circ\text{C}$	16	A
$I_{CM}$	$T_C = 25^\circ\text{C}$ , $V_{GE} = 20\text{V}$ , 1ms	140	A
<b>SSOA</b>	$V_{GE} = 20\text{V}$ , $T_{VJ} = 125^\circ\text{C}$ , $R_G = 5\Omega$	$I_{CM} = 160$	A
<b>(RBSOA)</b>	Clamped Inductive Load	$V_{CE} \leq 0.8 \cdot V_{CES}$	
$P_c$	$T_C = 25^\circ\text{C}$	114	W
$T_J$		-55 ... +150	°C
$T_{JM}$		150	°C
$T_{stg}$		-55 ... +150	°C
$T_L$	1.6 mm (0.062 in.) from Case for 10s	300	°C
$T_{SOLD}$	Plastic Body for 10s	260	°C
$F_c$	Mounting Force	20..120/4.5..27	Nm/lb-in.
$V_{ISOL}$	50/60Hz, 1 Minute	4000	V~
<b>Weight</b>		5	g

**ISOPLUS i4-Pak™**



1 = Gate      5 = Collector  
2 = Emitter

**Features**

- Silicon Chip on Direct-Copper Bond (DCB) Substrate
- Isolated Mounting Surface
- 4000V Electrical Isolation
- High Peak Current Capability
- Low Saturation Voltage
- Molding Epoxies Meet UL 94 V-0 Flammability Classification

**Applications**

- Capacitor Discharge
- Pulser Circuits

**Advantages**

- High Power Density
- Easy to Mount


Symbol	Test Conditions ( $T_J = 25^\circ\text{C}$ , Unless Otherwise Specified)	Characteristic Values		
		Min.	Typ.	Max.
$BV_{CES}$	$I_C = 1\text{mA}$ , $V_{GE} = 0\text{V}$	3000		V
$V_{GE(th)}$	$I_C = 250\mu\text{A}$ , $V_{CE} = V_{GE}$	3.0		V
$I_{CES}$	$V_{CE} = 0.8 \cdot V_{CES}$ , $V_{GE} = 0\text{V}$ Note 2, $T_J = 125^\circ\text{C}$		50 μA 1 mA	
$I_{GES}$	$V_{CE} = 0\text{V}$ , $V_{GE} = \pm 20\text{V}$		±100 nA	
$V_{CE(sat)}$	$I_C = 25\text{A}$ , $V_{GE} = 15\text{V}$ , Note 1 $I_C = 75\text{A}$		3.0 V 5.5 V	

Symbol	Test Conditions (T <sub>J</sub> = 25°C, Unless Otherwise Specified)	Characteristic Values		
		Min.	Typ.	Max.
g <sub>fs</sub>	I <sub>C</sub> = 50A, V <sub>CE</sub> = 10V, Note 1	16	26	S
I <sub>C(ON)</sub>	V <sub>GE</sub> = 15V, V <sub>CE</sub> = 20V, Note 1	240		A
C <sub>ies</sub>	V <sub>CE</sub> = 15V, V <sub>GE</sub> = 20V, f = 1MHz	2970		pF
C <sub>oes</sub>		98		pF
C <sub>res</sub>		36		pF
Q <sub>g(on)</sub>	I <sub>C</sub> = 50A, V <sub>GE</sub> = 15V, V <sub>CE</sub> = 0.5 • V <sub>CES</sub>	75		nC
Q <sub>ge</sub>		15		nC
Q <sub>gc</sub>		30		nC
t <sub>d(on)</sub>	Resistive Switching Times I <sub>C</sub> = 25A, V <sub>GE</sub> = 15V V <sub>CE</sub> = 1500V, R <sub>G</sub> = 5Ω	70		ns
t <sub>r</sub>		240		ns
t <sub>d(off)</sub>		220		ns
t <sub>f</sub>		500		ns
R <sub>thJC</sub>		0.15	1.10 °C/W	
R <sub>thCS</sub>		30	°C/W	
R <sub>thJA</sub>			°C/W	

## Notes:

1. Pulse test, t < 300μs, duty cycle, d < 2%.
2. Device must be heatsunk for high-temperature leakage current measurements to avoid thermal runaway.

ISOPLUS i4-Pak™ (HV) Outline



SYM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	.190	.205	4.83	5.21
A1	.102	.118	2.59	3.00
A2	.046	.085	1.17	2.16
b	.045	.055	1.14	1.40
b1	.058	.068	1.47	1.73
C	.020	.029	0.51	0.74
D	.819	.840	20.80	21.34
E	.770	.799	19.56	20.29
e	.150 BSC		3.81 BSC	
e1	.450BSC		11.43 BSC	
L	.780	.840	19.81	21.34
L1	.083	.102	2.11	2.59
Q	.210	.244	5.33	6.20
R	.100	.180	2.54	4.57
S	.660	.690	16.76	17.53
T	.590	.620	14.99	15.75
U	.065	.080	1.65	2.03



---

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for IGBT Transistors category:*

*Click to view products by IXYS manufacturer:*

Other Similar products are found below :

[748152A](#) [APT20GT60BRDQ1G](#) [APT50GT60BRG](#) [NGTB10N60FG](#) [STGFW20V60DF](#) [APT30GP60BG](#) [APT45GR65B2DU30](#)  
[GT50JR22\(STA1ES\)](#) [TIG058E8-TL-H](#) [IGW40N120H3FKSA1](#) [VS-CPV364M4KPBF](#) [NGTB25N120FL2WAG](#) [NGTG40N120FL2WG](#)  
[RJH60F3DPQ-A0#T0](#) [APT40GR120B2SCD10](#) [APT15GT120BRG](#) [APT20GT60BRG](#) [NGTB75N65FL2WAG](#) [NGTG15N120FL2WG](#)  
[IXA30RG1200DHGLB](#) [IXA40RG1200DHGLB](#) [APT70GR65B2DU40](#) [NTE3320](#) [QP12W05S-37A](#) [IHFW40N65R5SXKSA1](#) [APT70GR120J](#)  
[APT35GP120JDQ2](#) [IKZA40N65RH5XKSA1](#) [IKFW75N65ES5XKSA1](#) [IKFW50N65ES5XKSA1](#) [IKFW50N65EH5XKSA1](#)  
[IKFW40N65ES5XKSA1](#) [IKFW60N65ES5XKSA1](#) [IMBG120R090M1HXTMA1](#) [IMBG120R220M1HXTMA1](#) [XD15H120CX1](#)  
[XD25H120CX0](#) [XP15PJS120CL1B1](#) [IGW30N60H3FKSA1](#) [STGWA8M120DF3](#) [IGW08T120FKSA1](#) [IGW75N60H3FKSA1](#)  
[FGH60N60SMD\\_F085](#) [FGH75T65UPD](#) [STGWA15H120F2](#) [IKA10N60TXKSA1](#) [IHW20N120R5XKSA1](#) [RJH60D2DPP-M0#T2](#)  
[IKP20N60TXKSA1](#) [IHW20N65R5XKSA1](#)