


# GenX3™ 600V IGBT

## IXGK320N60A3 IXGX320N60A3


$V_{CES} = 600V$   
 $I_{C110} = 210A$   
 $V_{CE(sat)} \leq 1.30V$

Ultra-Low  $V_{sat}$  PT IGBTs for  
up to 5kHz Switching




| Symbol                        | Test Conditions   | Maximum Ratings                         |            |
|-------------------------------|---|---|------------|
| $V_{CES}$                     | $T_J = 25^\circ C$ to $150^\circ C$   | 600                                     | V          |
| $V_{CGR}$                     | $T_J = 25^\circ C$ to $150^\circ C$ , $R_{GE} = 1M\Omega$                           | 600                                     | V          |
| $V_{GES}$                     | Continuous  | $\pm 20$                                | V          |
| $V_{GEM}$                     | Transient   | $\pm 30$                                | V          |
| $I_{C25}$                     | $T_C = 25^\circ C$ (Chip Capability)  | 320                                     | A          |
| $I_{C110}$                    | $T_C = 110^\circ C$   | 210                                     | A          |
| $I_{LRMS}$                    | Terminal Current Limit  | 160                                     | A          |
| $I_{CM}$                      | $T_C = 25^\circ C$ , 1ms  | 700                                     | A          |
| <b>SSOA</b><br><b>(RBSOA)</b> | $V_{GE} = 15V$ , $T_{VJ} = 125^\circ C$ , $R_G = 1\Omega$<br>Clamped Inductive Load | $I_{CM} = 320$<br>@ $0.8 \cdot V_{CES}$ | A          |
| $P_C$                         | $T_C = 25^\circ C$  | 1000                                    | W          |
| $T_J$                         |   | -55 ... +150                            | $^\circ C$ |
| $T_{JM}$                      |   | 150                                     | $^\circ C$ |
| $T_{stg}$                     |   | -55 ... +150                            | $^\circ C$ |
| $T_L$                         | Maximum Lead Temperature for Soldering  | 300                                     | $^\circ C$ |
| $T_{SOLD}$                    | 1.6 mm (0.062 in.) from Case for 10   | 260                                     | $^\circ C$ |
| $M_d$                         | Mounting Torque (IXGK)  | 1.13/10                                 | Nm/lb.in   |
| $F_C$                         | Mounting Force (IXGX)   | 20..120/4.5..27                         | N/lb       |
| <b>Weight</b>                 | TO-264  | 10                                      | g          |
|                               | PLUS247   | 6                                       | g          |

### TO-264 (IXGK)



### PLUS247 (IXGX)



G = Gate                      E = Emitter  
C = Collector                Tab = Collector

### Features

- Optimized for Low Conduction Losses
- High Avalanche Capability
- International Standard Packages

### Advantages

- High Power Density
- Low Gate Drive Requirement

### Applications


- Power Inverters
- UPS
- Motor Drives
- SMPS
- PFC Circuits
- Battery Chargers
- Welding Machines
- Lamp Ballasts
- Inrush Current Protection Circuits

| Symbol        | Test Conditions<br>( $T_J = 25^\circ C$ , Unless Otherwise Specified) | Characteristic Values |      |                       |
|---------------|---|-----------------------|------|-----------------------|
|               |   | Min.                  | Typ. | Max.                  |
| $BV_{CES}$    | $I_C = 1mA$ , $V_{GE} = 0V$   | 600                   |      | V                     |
| $V_{GE(th)}$  | $I_C = 4mA$ , $V_{CE} = V_{GE}$                                       | 3.0                   |      | 5.5 V                 |
| $I_{CES}$     | $V_{CE} = V_{CES}$ , $V_{GE} = 0V$<br>$T_J = 125^\circ C$             |                       |      | 150 $\mu A$<br>1.5 mA |
| $I_{GES}$     | $V_{CE} = 0V$ , $V_{GE} = \pm 20V$                                    |                       |      | $\pm 400$ nA          |
| $V_{CE(sat)}$ | $I_C = 100A$ , $V_{GE} = 15V$ , Note 1<br>$I_C = 320A$                | 1.05<br>1.46          | 1.30 | V<br>V                |

| Symbol       | Test Conditions<br>( $T_J = 25^\circ\text{C}$ , Unless Otherwise Specified) | Characteristic Values                   |      |                          |
|--------------|---|---|------|--------------------------|
|              |   | Min.                                    | Typ. | Max.                     |
| $g_{fs}$     | $I_C = 60\text{A}, V_{CE} = 10\text{V}$ , Note 1                            | 75                                      | 125  | S                        |
| $C_{ies}$    | $V_{CE} = 25\text{V}, V_{GE} = 0\text{V}, f = 1\text{MHz}$                  |   | 18   | nF                       |
| $C_{oes}$    |   |   | 985  | pF                       |
| $C_{res}$    |   |   | 150  | pF                       |
| $Q_{g(on)}$  | $I_C = 80\text{A}, V_{GE} = 15\text{V}, V_{CE} = 0.5 \cdot V_{CES}$         |   | 560  | nC                       |
| $Q_{ge}$     |   |   | 94   | nC                       |
| $Q_{gc}$     |   |   | 195  | nC                       |
| $t_{d(on)}$  | <b>Resistive load, <math>T_J = 25^\circ\text{C}</math></b>                  |   | 63   | ns                       |
| $t_r$        |   | $I_C = 80\text{A}, V_{GE} = 15\text{V}$ | 68   | ns                       |
| $t_{d(off)}$ | $V_{CE} = 400\text{V}, R_G = 1\Omega$                                       |   | 290  | ns                       |
| $t_f$        |   |   | 740  | ns                       |
| $t_{d(on)}$  | <b>Resistive load, <math>T_J = 125^\circ\text{C}</math></b>                 |   | 62   | ns                       |
| $t_r$        |   | $I_C = 80\text{A}, V_{GE} = 15\text{V}$ | 77   | ns                       |
| $t_{d(off)}$ | $V_{CE} = 400\text{V}, R_G = 1\Omega$                                       |   | 330  | ns                       |
| $t_f$        |   |   | 1540 | ns                       |
| $R_{thJC}$   |   |   |      | 0.125 $^\circ\text{C/W}$ |
| $R_{thCK}$   |   | 0.15                                    |      | $^\circ\text{C/W}$       |

Note 1. Pulse test,  $t \leq 300\mu\text{s}$ , duty cycle,  $d \leq 2\%$ .


### TO-264 Outline



Terminals: 1 - Gate 2, 4 - Collector  
3 - Emitter

| SYM | INCHES   |       | MILLIMETERS |       |
|-----|----------|-------|-------------|-------|
|     | MIN      | MAX   | MIN         | MAX   |
| A   | .185     | .209  | 4.70        | 5.31  |
| A1  | .102     | .118  | 2.59        | 3.00  |
| b   | .037     | .055  | 0.94        | 1.40  |
| b1  | .087     | .102  | 2.21        | 2.59  |
| b2  | .110     | .126  | 2.79        | 3.20  |
| c   | .017     | .029  | 0.43        | 0.74  |
| D   | 1.007    | 1.047 | 25.58       | 26.59 |
| E   | .760     | .799  | 19.30       | 20.29 |
| e   | .215 BSC |       | 5.46 BSC    |       |
| J   | .000     | .010  | 0.00        | 0.25  |
| K   | .000     | .010  | 0.00        | 0.25  |
| L   | .779     | .842  | 19.79       | 21.39 |
| L1  | .087     | .102  | 2.21        | 2.59  |
| ØP  | .122     | .138  | 3.10        | 3.51  |
| Q   | .240     | .256  | 6.10        | 6.50  |
| Q1  | .330     | .346  | 8.38        | 8.79  |
| ØR  | .155     | .187  | 3.94        | 4.75  |
| ØR1 | .085     | .093  | 2.16        | 2.36  |
| S   | .243     | .253  | 6.17        | 6.43  |

### PLUS247™ Outline



Terminals: 1 - Gate  
2 - Collector  
3 - Emitter

| Dim.           | Millimeter |       | Inches   |       |
|----------------|------------|-------|----------|-------|
|                | Min.       | Max.  | Min.     | Max.  |
| A              | 4.83       | 5.21  | .190     | .205  |
| A <sub>1</sub> | 2.29       | 2.54  | .090     | .100  |
| A <sub>2</sub> | 1.91       | 2.16  | .075     | .085  |
| b              | 1.14       | 1.40  | .045     | .055  |
| b <sub>1</sub> | 1.91       | 2.13  | .075     | .084  |
| b <sub>2</sub> | 2.92       | 3.12  | .115     | .123  |
| C              | 0.61       | 0.80  | .024     | .031  |
| D              | 20.80      | 21.34 | .819     | .840  |
| E              | 15.75      | 16.13 | .620     | .635  |
| e              | 5.45 BSC   |       | .215 BSC |       |
| L              | 19.81      | 20.32 | .780     | .800  |
| L1             | 3.81       | 4.32  | .150     | .170  |
| Q              | 5.59       | 6.20  | .220     | 0.244 |

IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

IXYS MOSFETs and IGBTs are covered 4,835,592 4,931,844 5,049,961 5,237,481 6,162,665 6,404,065 B1 6,683,344 6,727,585 7,005,734 B2 7,157,338 B2  
by one or more of the following U.S. patents: 4,860,072 5,017,508 5,063,307 5,381,025 6,259,123 B1 6,534,343 6,710,405 B2 6,759,692 7,063,975 B2  
4,881,106 5,034,796 5,187,117 5,486,715 6,306,728 B1 6,583,505 6,710,463 6,771,478 B2 7,071,537

Fig. 1. Extended Output Characteristics @  $T_J = 25^\circ\text{C}$




Fig. 2. Output Characteristics @  $T_J = 125^\circ\text{C}$




Fig. 3. Dependence of  $V_{CE(sat)}$  on Junction Temperature




Fig. 4. Collector-to-Emitter Voltage vs. Gate-to-Emitter Voltage




Fig. 5. Input Admittance







Fig. 6. Transconductance




**Fig. 7. Gate Charge**




**Fig. 8. Capacitance**




**Fig. 9. Reverse-Bias Safe Operating Area**




**Fig. 10. Maximum Transient Thermal Impedance**




**Fig.11. Resistive Turn-on Rise Time vs. Junction Temperature**




**Fig. 12. Resistive Turn-on Rise Time vs. Collector Current**




**Fig. 13. Resistive Turn-on Switching Times vs. Gate Resistance**




**Fig. 14. Resistive Turn-off Switching Times vs. Junction Temperature**



**Fig. 15. Resistive Turn-off Switching Times vs. Collector Current**



**Fig. 16. Resistive Turn-off Switching Times vs. Gate Resistance**



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [IGBT Transistors](#) category:*

*Click to view products by [IXYS](#) manufacturer:*

Other Similar products are found below :

[748152A](#) [APT20GT60BRDQ1G](#) [APT50GT60BRG](#) [NGTB10N60FG](#) [STGFW20V60DF](#) [APT30GP60BG](#) [APT45GR65B2DU30](#)  
[GT50JR22\(STA1ES\)](#) [TIG058E8-TL-H](#) [IGW40N120H3FKSA1](#) [VS-CPV364M4KPBF](#) [NGTB25N120FL2WAG](#) [NGTG40N120FL2WG](#)  
[RJH60F3DPQ-A0#T0](#) [APT40GR120B2SCD10](#) [APT15GT120BRG](#) [APT20GT60BRG](#) [NGTB75N65FL2WAG](#) [NGTG15N120FL2WG](#)  
[IXA30RG1200DHGLB](#) [IXA40RG1200DHGLB](#) [APT70GR65B2DU40](#) [NTE3320](#) [QP12W05S-37A](#) [IHF40N65R5SXXSA1](#) [APT70GR120J](#)  
[APT35GP120JDQ2](#) [IKZA40N65RH5XKSA1](#) [IKFW75N65ES5XKSA1](#) [IKFW50N65ES5XKSA1](#) [IKFW50N65EH5XKSA1](#)  
[IKFW40N65ES5XKSA1](#) [IKFW60N65ES5XKSA1](#) [IMBG120R090M1HXTMA1](#) [IMBG120R220M1HXTMA1](#) [XD15H120CX1](#)  
[XD25H120CX0](#) [XP15PJS120CL1B1](#) [IGW30N60H3FKSA1](#) [STGWA8M120DF3](#) [IGW08T120FKSA1](#) [IGW75N60H3FKSA1](#)  
[FGH60N60SMD\\_F085](#) [FGH75T65UPD](#) [STGWA15H120F2](#) [IKA10N60TXKSA1](#) [IHW20N120R5XKSA1](#) [RJH60D2DPP-M0#T2](#)  
[IKP20N60TXKSA1](#) [IHW20N65R5XKSA1](#)