




PolarHV™ Power MOSFET

IXTA 8N50P IXTP 8N50P

V_{DSS} = 500 V
 I_{D25} = 8 A
 $R_{DS(on)}$ ≤ 0.8 Ω

N-Channel Enhancement Mode
Avalanche Rated



G = Gate D = Drain
 S = Source TAB = Drain

Symbol	Test Conditions	Maximum Ratings		
V_{DSS}	$T_J = 25^\circ C$ to $150^\circ C$	500	V	
V_{DGR}	$T_J = 25^\circ C$ to $150^\circ C$; $R_{GS} = 1 M\Omega$	500	V	
V_{GS}	Continuous	± 30	V	
V_{GSM}	Transient	± 40	V	
I_{D25}	$T_c = 25^\circ C$	8	A	
I_{DM}	$T_c = 25^\circ C$, pulse width limited by T_{JM}	14	A	
I_{AR}	$T_c = 25^\circ C$	8	A	
E_{AR}	$T_c = 25^\circ C$	20	mJ	
E_{AS}	$T_c = 25^\circ C$	400	mJ	
dv/dt	$I_s \leq I_{DM}$, $di/dt \leq 100 A/\mu s$, $V_{DD} \leq V_{DSS}$, $T_j \leq 150^\circ C$, $R_G = 18 \Omega$	10	V/ns	
P_D	$T_c = 25^\circ C$	150	W	
T_J		-55 ... +150	°C	
T_{JM}		150	°C	
T_{stg}		-55 ... +150	°C	
T_L	1.6 mm (0.062 in.) from case for 10 s	300	°C	
T_{SOLD}	Plastic body for 10 s	260	°C	
M_d	Mounting torque (TO-220)	1.13/10	Nm/lb.in.	
Weight	TO-220	4	g	
	TO-263	3	g	

Symbol	Test Conditions ($T_J = 25^\circ C$ unless otherwise specified)	Characteristic Values		
		Min.	Typ.	Max.
BV_{DSS}	$V_{GS} = 0 V$, $I_D = 250 \mu A$	500		V
$V_{GS(th)}$	$V_{DS} = V_{GS}$, $I_D = 100 \mu A$	3.0		V
I_{GSS}	$V_{GS} = \pm 30 V_{DC}$, $V_{DS} = 0$		± 100	nA
I_{DSS}	$V_{DS} = V_{DSS}$ $V_{GS} = 0 V$		5 50	μA μA
$R_{DS(on)}$	$V_{GS} = 10 V$, $I_D = 0.5 I_{D25}$ Pulse test, $t \leq 300 \mu s$, duty cycle $d \leq 2 \%$		0.8	Ω

Features

- International standard packages
- Unclamped Inductive Switching (UIS) rated
- Low package inductance
 - easy to drive and to protect

Advantages


- Easy to mount
- Space savings
- High power density

Symbol **Test Conditions**
Characteristic Values
 $(T_J = 25^\circ C \text{ unless otherwise specified})$
Min. **Typ.** **Max.**


g_{fs}	$V_{DS} = 10 V; I_D = 0.5 I_{D25}$, pulse test	5	8	S
C_{iss} C_{oss} C_{rss}	$V_{GS} = 0 V, V_{DS} = 25 V, f = 1 \text{ MHz}$	1050	pF	
		120	pF	
		12	pF	
$t_{d(on)}$ t_r $t_{d(off)}$ t_f	$V_{GS} = 10 V, V_{DS} = 0.5 V_{DSS}, I_D = I_{D25}$ $R_G = 18 \Omega$ (External)	22	ns	
		28	ns	
		65	ns	
		23	ns	
$Q_{g(on)}$ Q_{gs} Q_{gd}	$V_{GS} = 10 V, V_{DS} = 0.5 V_{DSS}, I_D = 0.5 I_{D25}$	20	nC	
		7	nC	
		7	nC	
R_{thJC}			0.83 $^\circ C/W$	
R_{thcs}	(TO-220)	0.25	$^\circ C/W$	

Source-Drain Diode
Characteristic Values
 $(T_J = 25^\circ C, \text{ unless otherwise specified})$

Symbol	Test Conditions	Min.	Typ.	Max.
I_s	$V_{GS} = 0 V$			8 A
I_{SM}	Repetitive			14 A
V_{SD}	$I_F = I_s, V_{GS} = 0 V,$ Pulse test, $t \leq 300 \mu s$, duty cycle $d \leq 2\%$			1.5 V
t_{rr}	$I_F = 8 A, V_{GS} = 0 V, V_R = 100 V$ $-di/dt = 100 A/\mu s$	400		ns

TO-263 (IXTA) Outline


SYM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	.360	.390	9.06	4.83
A1	.080	.110	2.03	2.79
b	.020	.039	0.51	0.99
b2	.045	.055	1.14	1.40
c	.016	.029	0.40	0.74
c2	.045	.055	1.14	1.40
D	.340	.380	8.64	9.65
D1	.315	.350	8.00	8.89
E	.380	.410	9.65	10.41
E1	.245	.320	6.22	8.13
e	.100 BSC		2.54 BSC	
L	.575	.625	14.61	15.88
L1	.090	.110	2.29	2.79
L2	.040	.055	1.02	1.40
L3	.050	.070	1.27	1.78
L4	0	.005	0	0.13

TO-220 (IXTP) Outline

 Pins: 1 - Gate 2 - Drain
 3 - Source 4 - Drain

SYM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	.170	.190	4.32	4.83
b	.025	.040	0.64	1.02
b1	.045	.065	1.15	1.65
c	.014	.022	0.35	0.56
D	.580	.630	14.73	16.00
E	.390	.420	9.91	10.66
e	.100 BSC		2.54 BSC	
F	.045	.055	1.14	1.40
H1	.230	.270	5.85	6.85
J1	.090	.110	2.29	2.79
k	0	.015	0	0.38
L	.500	.550	12.70	13.97
L1	.110	.230	2.79	5.84
$\emptyset P$.139	.161	3.53	4.08
Q	.100	.125	2.54	3.18

IXYS reserves the right to change limits, test conditions, and dimensions.

 IXYS MOSFETs and IGBTs are covered by 4,835,592 4,931,844 5,049,961 5,237,481 6,162,665 6,404,065 B1 6,683,344 6,727,585
 one or more of the following U.S. patents: 4,850,072 5,017,508 5,063,307 5,381,025 6,259,123 B1 6,534,343 6,710,405B2 6,759,692
 4,881,106 5,034,796 5,187,117 5,486,715 6,306,728 B1 6,583,505 6,710,463 6,771,478 B2







Fig. 1. Output Characteristics
@ 25°C

Fig. 2. Extended Output Characteristics
@ 25°C

Fig. 3. Output Characteristics
@ 125°C

Fig. 4. $R_{DS(on)}$ Normalized to 0.5 I_{D25} Value vs. Junction Temperature

Fig. 5. $R_{DS(on)}$ Normalized to 0.5 I_{D25} Value vs. I_D

Fig. 6. Drain Current vs. Case Temperature









Fig. 7. Input Admittance**Fig. 9. Source Current vs. Source-To-Drain Voltage****Fig. 11. Capacitance****Fig. 8. Transconductance****Fig. 10. Gate Charge****Fig. 12. Forward-Bias Safe Operating Area**

Fig. 13. Maximum Transient Thermal Resistance





Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [MOSFET](#) category:

Click to view products by [IXYS](#) manufacturer:

Other Similar products are found below :

[614233C](#) [648584F](#) [IRFD120](#) [JANTX2N5237](#) [FCA20N60_F109](#) [FDZ595PZ](#) [2SK2545\(Q,T\)](#) [405094E](#) [423220D](#) [TPCC8103,L1Q\(CM](#)
[MIC4420CM-TR](#) [VN1206L](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [SSM6J414TU,LF\(T](#) [751625C](#) [BUK954R8-60E](#) [NTE6400](#) [SQJ402EP-](#)
[T1-GE3](#) [2SK2614\(TE16L1,Q\)](#) [2N7002KW-FAI](#) [DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [ECH8691-TL-W](#) [FCAB21350L1](#) [P85W28HP2F-](#)
[7071](#) [DMN1053UCP4-7](#) [NTE221](#) [NTE222](#) [NTE2384](#) [NTE2903](#) [NTE2941](#) [NTE2945](#) [NTE2946](#) [NTE2960](#) [NTE2967](#) [NTE2969](#) [NTE2976](#)
[NTE6400A](#) [NTE2910](#) [NTE2916](#) [NTE2956](#) [NTE2911](#) [DMN2080UCB4-7](#) [TK10A80W,S4X\(S](#) [SSM6P69NU,LF](#) [DMP22D4UFO-7B](#)
[DMN1006UCA6-7](#) [DMN16M9UCA6-7](#)