



IGBT Modules

H Bridge

Short Circuit SOA Capability
Square RBSOA

I_{C25} = 125 A
 V_{CES} = 1200 V
 $V_{CE(sat)\text{typ.}}$ = 3.3 V



IGBTs

Symbol	Conditions	Maximum Ratings		
V_{CES}	$T_{VJ} = 25^\circ\text{C}$ to 150°C	1200		V
V_{GES}		± 20		V
I_{C25}	$T_C = 25^\circ\text{C}$	125		A
I_{C80}	$T_C = 80^\circ\text{C}$	85		A
I_{CM}	$V_{GE} = \pm 15 \text{ V}$; $R_G = 5.6 \Omega$; $T_{VJ} = 125^\circ\text{C}$	200		A
V_{CEK}	RBSOA; clamped inductive load; $L = 100 \mu\text{H}$		V_{CES}	
t_{sc}	$V_{CE} = 900 \text{ V}$; $V_{GE} = \pm 15 \text{ V}$; $R_G = 5.6 \Omega$; $T_{VJ} = 125^\circ\text{C}$ SCSOA; non-repetitive	10		μs
P_{tot}	$T_C = 25^\circ\text{C}$	640		W

Symbol	Conditions	Characteristic Values		
		($T_{VJ} = 25^\circ\text{C}$, unless otherwise specified)		
		min.	typ.	max.
$V_{CE(sat)}$	$I_C = 100 \text{ A}$; $V_{GE} = 15 \text{ V}$; $T_{VJ} = 25^\circ\text{C}$ $T_{VJ} = 125^\circ\text{C}$	3.3 4.0	3.9 V	V
$V_{GE(th)}$	$I_C = 4 \text{ mA}$; $V_{GE} = V_{CE}$	4.5	6.5	V
I_{CES}	$V_{CE} = V_{CES}$; $V_{GE} = 0 \text{ V}$; $T_{VJ} = 25^\circ\text{C}$ $T_{VJ} = 125^\circ\text{C}$	4.0	1.3 mA mA	mA
I_{GES}	$V_{CE} = 0 \text{ V}$; $V_{GE} = \pm 20 \text{ V}$		600	nA
$t_{d(on)}$ t_r $t_{d(off)}$ t_f E_{on} E_{off}	$\left. \begin{array}{l} \text{Inductive load, } T_{VJ} = 125^\circ\text{C} \\ V_{CE} = 600 \text{ V}; I_C = 100 \text{ A} \\ V_{GE} = \pm 15 \text{ V}; R_G = 5.6 \Omega \end{array} \right\}$	130 60 365 30 12.0 5.0	ns ns ns ns mJ mJ	
C_{ies}		6.5		nF
Q_{Gon}		1.1		μC
R_{thJC}			0.19	K/W

Features

- Fast NPT IGBTs
 - low saturation voltage
 - positive temperature coefficient for easy paralleling
 - fast switching
 - short tail current for optimized performance also in resonant circuits
- HiPerFRED™ diode:
 - fast reverse recovery
 - low operating forward voltage
 - low leakage current
- Industry Standard Package
 - solderable pins for PCB mounting
 - isolated copper base plate

Typical Applications

- motor control
 - . DC motor amature winding
 - . DC motor excitation winding
 - . synchronous motor excitation winding
- supply of transformer primary winding
- . power supplies
- . welding
- . X-ray
- . battery charger

Diodes


Symbol	Conditions	Maximum Ratings		
I _{F25}	T _C = 25°C	200	A	
I _{F80}	T _C = 80°C	130	A	

Symbol	Conditions	Characteristic Values		
		min.	typ.	max.
V _F	I _F = 100 A; V _{GE} = 0 V; T _{VJ} = 25°C T _{VJ} = 125°C	2.3 1.7	2.6 V	V
I _{RM} t _{rr}	I _F = 120 A; di _F /dt = -750 A/μs; T _{VJ} = 125°C V _R = 600 V; V _{GE} = 0 V	82 200	A ns	
R _{thJC}	(per diode)		0.3	K/W

Module


Symbol	Conditions	Maximum Ratings		
T _{VJ}	operating	-40...+125	°C	
T _{JM}		+150	°C	
T _{stg}		-40...+125	°C	
V _{ISOL}	I _{ISOL} ≤ 1 mA; 50/60 Hz	2500	V~	
M _d	Mounting torque (M5)	3 - 6	Nm	

Symbol	Conditions	Characteristic Values		
		min.	typ.	max.
R _{pin-chip}		1.8	mΩ	
d _s d _A	Creepage distance on surface Strike distance in air	10 10	mm mm	
R _{thCH}	with heatsink compound	0.01	K/W	
Weight		300	g	

Equivalent Circuits for Simulation**Conduction**


IGBT (typ. at V_{GE} = 15 V; T_J = 125°C)
V₀ = 2.05 V; R₀ = 19.5 mΩ

Free Wheeling Diode (typ. at T_J = 125°C)
V₀ = 1.27 V; R₀ = 4.3 mΩ

Thermal Response

IGBT (typ.)
C_{th1} = 0.409 J/K; R_{th1} = 0.14 K/W
C_{th2} = 2.203 J/K; R_{th2} = 0.05 K/W

Free Wheeling Diode (typ.)
C_{th1} = 0.301 J/K; R_{th1} = 0.24 K/W
C_{th2} = 2.005 J/K; R_{th2} = 0.062 K/W

Dimensions in mm (1 mm = 0.0394")

pins 5, 6, 7, 8 and 17 for MWI only

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for IGBT Modules category:

Click to view products by IXYS manufacturer:

Other Similar products are found below :

[F3L400R07ME4_B22](#) [F4-50R07W2H3_B51](#) [FB15R06W1E3](#) [FB20R06W1E3_B11](#) [FD1000R33HE3-K](#) [FD400R33KF2C-K](#)
[FD401R17KF6C_B2](#) [FD-DF80R12W1H3_B52](#) [FF200R06YE3](#) [FF300R12KE4_E](#) [FF450R12ME4P](#) [FF600R12IP4V](#) [FP10R06W1E3_B11](#)
[FP20R06W1E3](#) [FP50R12KT3](#) [FP75R07N2E4_B11](#) [FS10R12YE3](#) [FS150R07PE4](#) [FS150R12PT4](#) [FS200R12KT4R](#) [FS50R07N2E4_B11](#)
[FZ1000R33HE3](#) [FZ1800R17KF4](#) [DD250S65K3](#) [DF1000R17IE4](#) [DF1000R17IE4D_B2](#) [DF1400R12IP4D](#) [DF200R12PT4_B6](#)
[DF400R07PE4R_B6](#) [BSM75GB120DN2_E3223c-Se](#) [F3L300R12ME4_B22](#) [F3L75R07W2E3_B11](#) [F4-50R12KS4_B11](#)
[F475R07W1H3B11ABOMA1](#) [FD1400R12IP4D](#) [FD200R12PT4_B6](#) [FD800R33KF2C-K](#) [FF1200R17KP4_B2](#) [FF300R17KE3_S4](#)
[FF300R17ME4_B11](#) [FF401R17KF6C_B2](#) [FF650R17IE4D_B2](#) [FF900R12IP4D](#) [FF900R12IP4DV](#) [STGIF7CH60TS-L](#) [FP50R07N2E4_B11](#)
[FS100R07PE4](#) [FS150R07N3E4_B11](#) [FS150R17N3E4](#) [FS150R17PE4](#)