



# IGBT Modules

## Sixpack

Short Circuit SOA Capability  
Square RBSOA

**I<sub>C25</sub>** = 160 A  
**V<sub>CES</sub>** = 1200 V  
**V<sub>CE(sat)</sub> typ.** = 2.2 V



See outline drawing for pin arrangement

### IGBTs

| Symbol                     | Conditions  | Maximum Ratings  |  |    |
|----------------------------|---|--|--|----|
| V <sub>CES</sub>           | T <sub>VJ</sub> = 25°C to 150°C   | 1200   |  | V  |
| V <sub>GES</sub>           |   | ± 20   |  | V  |
| I <sub>C25</sub>           | T <sub>C</sub> = 25°C   | 160  |  | A  |
| I <sub>C80</sub>           | T <sub>C</sub> = 80°C   | 110  |  | A  |
| RBSOA                      | V <sub>GE</sub> = ±15 V; R <sub>G</sub> = 6.8 Ω; T <sub>VJ</sub> = 125°C<br>Clamped inductive load; L = 100 μH                  | I <sub>CM</sub> = 200<br>V <sub>CEK</sub> ≤ V <sub>CES</sub> |  | A  |
| t <sub>sc</sub><br>(SCSOA) | V <sub>CE</sub> = V <sub>CES</sub> ; V <sub>GE</sub> = ±15 V; R <sub>G</sub> = 6.8 Ω; T <sub>VJ</sub> = 125°C<br>non-repetitive | 10   |  | μs |
| P <sub>tot</sub>           | T <sub>C</sub> = 25°C   | 640  |  | W  |

| Symbol   | Conditions  | Characteristic Values                                |      |                                  |
|--|---|--|------|----------------------------------|
|  |   | (T <sub>VJ</sub> = 25°C, unless otherwise specified) |      |                                  |
|  |   | min.   | typ. | max.                             |
| V <sub>CE(sat)</sub>   | I <sub>C</sub> = 100 A; V <sub>GE</sub> = 15 V; T <sub>VJ</sub> = 25°C<br>T <sub>VJ</sub> = 125°C   | 2.2<br>2.5   | 2.6  | V                                |
| V <sub>GE(th)</sub>  | I <sub>C</sub> = 4 mA; V <sub>GE</sub> = V <sub>CE</sub>  | 4.5  | 6.5  | V                                |
| I <sub>CES</sub>   | V <sub>CE</sub> = V <sub>CES</sub> ; V <sub>GE</sub> = 0 V; T <sub>VJ</sub> = 25°C<br>T <sub>VJ</sub> = 125°C                                 | 4  | 6.3  | mA                               |
| I <sub>GES</sub>   | V <sub>CE</sub> = 0 V; V <sub>GE</sub> = ± 20 V   |  | 400  | nA                               |
| t <sub>d(on)</sub><br>t <sub>r</sub><br>t <sub>d(off)</sub><br>t <sub>f</sub><br>E <sub>on</sub><br>E <sub>off</sub> | Inductive load, T <sub>VJ</sub> = 125°C<br>V <sub>CE</sub> = 600 V; I <sub>C</sub> = 100 A<br>V <sub>GE</sub> = ±15 V; R <sub>G</sub> = 6.8 Ω | 100<br>60<br>600<br>90<br>16.1<br>14.6               |      | ns<br>ns<br>ns<br>ns<br>mJ<br>mJ |
| C <sub>ies</sub><br>Q <sub>Gon</sub>   | V <sub>CE</sub> = 25 V; V <sub>GE</sub> = 0 V; f = 1 MHz<br>V <sub>CE</sub> = 600 V; V <sub>GE</sub> = 15 V; I <sub>C</sub> = 100 A           | 6.5<br>475   |      | nF<br>nC                         |
| R <sub>thJC</sub>  | (per IGBT)  |  | 0.19 | K/W                              |

### Features

- €NPT IGBT technology
- €low saturation voltage
- €low switching losses
- €switching frequency up to 30 kHz
- €square RBSOA, no latch up
- €high short circuit capability
- €positive temperature coefficient for easy parallelling
- €MOS input, voltage controlled
- €ultra fast free wheeling diodes
- €solderable pins for PCB mounting
- €package with copper base plate

### Advantages

- €space savings
- €reduced protection circuits
- €package designed for wave soldering

### Typical Applications

- €AC motor control
- €AC servo and robot drives
- €power supplies

## Diodes

| Symbol           | Conditions            | Maximum Ratings |   |  |
|------------------|-----------------------|-----------------|---|--|
| I <sub>F25</sub> | T <sub>C</sub> = 25°C | 200             | A |  |
| I <sub>F80</sub> | T <sub>C</sub> = 80°C | 130             | A |  |


| Symbol                             | Conditions  | Characteristic Values |      |      |
|------------------------------------|---|-----------------------|------|------|
|                                    |   | min.                  | typ. | max. |
| V <sub>F</sub>                     | I <sub>F</sub> = 100 A; V <sub>GE</sub> = 0 V; T <sub>VJ</sub> = 25°C<br>T <sub>VJ</sub> = 125°C                                  | 2.3                   | 2.6  | V    |
|                                    |   | 1.7                   |      | V    |
| I <sub>RM</sub><br>t <sub>rr</sub> | I <sub>F</sub> = 120 A; di <sub>F</sub> /dt = -750 A/μs; T <sub>VJ</sub> = 125°C<br>V <sub>R</sub> = 600 V; V <sub>GE</sub> = 0 V | 82                    |      | A    |
|                                    |   | 200                   |      | ns   |
| R <sub>thJC</sub>                  | (per diode)   |                       | 0.3  | K/W  |

## Module

| Symbol            | Conditions                         | Maximum Ratings |    |  |
|-------------------|------------------------------------|-----------------|----|--|
| T <sub>VJ</sub>   | operating                          | -40...+125      | °C |  |
| T <sub>JM</sub>   |                                    | +150            | °C |  |
| T <sub>stg</sub>  |                                    | -40...+125      | °C |  |
| V <sub>ISOL</sub> | I <sub>ISOL</sub> ≤ 1 mA; 50/60 Hz | 2500            | V~ |  |
| M <sub>d</sub>    | Mounting torque (M5)               | 3 - 6           | Nm |  |

| Symbol                | Conditions                   | Characteristic Values |      |      |
|-----------------------|------------------------------|-----------------------|------|------|
|                       |                              | min.                  | typ. | max. |
| R <sub>pin-chip</sub> |                              |                       | 1.8  | mΩ   |
| d <sub>s</sub>        | Creepage distance on surface | 10                    |      | mm   |
| d <sub>A</sub>        | Strike distance in air       | 10                    |      | mm   |
| R <sub>thCH</sub>     | with heatsink compound       | 0.01                  |      | K/W  |
| Weight                |                              | 300                   |      | g    |


## Dimensions in mm (1 mm = 0.0394")



IXYS reserves the right to change limits, test conditions and dimensions.

## Equivalent Circuits for Simulation


## Conduction



IGBT (typ. at V<sub>GE</sub> = 15 V; T<sub>J</sub> = 125°C)  
V<sub>0</sub> = 1.3 V; R<sub>0</sub> = 12 mΩ

Free Wheeling Diode (typ. at T<sub>J</sub> = 125°C)  
V<sub>0</sub> = 1.27 V; R<sub>0</sub> = 4.3 mΩ

## Thermal Response



IGBT (typ.)  
C<sub>th1</sub> = 0.397 J/K; R<sub>th1</sub> = 0.141 K/W  
C<sub>th2</sub> = 2.243 J/K; R<sub>th2</sub> = 0.049 K/W

Free Wheeling Diode (typ.)  
C<sub>th1</sub> = 0.301 J/K; R<sub>th1</sub> = 0.238 K/W  
C<sub>th2</sub> = 2.005 J/K; R<sub>th2</sub> = 0.062 K/W




Fig. 1 Typ. output characteristics




Fig. 2 Typ. output characteristics




Fig. 3 Typ. transfer characteristics




Fig. 4 Typ. forward characteristics of free wheeling diode




Fig. 5 Typ. turn on gate charge




Fig. 6 Typ. turn off characteristics of free wheeling diode




Fig. 7 Typ. turn on energy and switching times versus collector current




Fig. 8 Typ. turn off energy and switching times versus collector current




Fig. 9 Typ. turn on energy and switching times versus gate resistor




Fig. 10 Typ. turn off energy and switching times versus gate resistor




Fig. 11 Reverse biased safe operating area RBSOA




Fig. 12 Typ. transient thermal impedance

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for Discrete Semiconductor Modules category:***

***Click to view products by IXYS manufacturer:***

Other Similar products are found below :

[M252511FV](#) [M254043](#) [DD260N12K-A](#) [DD285N02K](#) [DD380N16A](#) [DDB6U144N16R](#) [DDB6U145N16L](#) [APT20M11JFLL](#)  
[APT2X101DL40J](#) [APT2X21DC60J](#) [APT2X30D40J](#) [APT2X30D60J](#) [APT2X31DQ120J](#) [APT39M60J](#) [APT47M60J](#) [APT50DF170HJ](#)  
[APT50M50JLL](#) [APT50M75JLLU3](#) [APT50N60JCCU2](#) [APT58M80J](#) [APT80F60J](#) [DZ540N26K](#) [B522F-2-YEC](#) [MSTC90-16](#)  
[MT16HTF12864AZ-800G1](#) [MT18HTF12872PZ-667G1](#) [MT18HTF25672FDZ-667H1D6](#) [MT18HTF25672PZ-80EH1](#) [MT18RTF25672FDZ-667H1D6](#) [MT36HTF51272FZ-667H1D4](#) [MT36HTF51272FZ-667H1D6](#) [MT8HTF12864HTZ-667H1](#) [MT9HTF6472PZ-667G1](#)  
[MT9HVF12872PZ-80EH1](#) [MT9HVF6472PZ-667G1](#) [ND104N16K](#) [25.163.0653.1](#) [25.163.2453.0](#) [25.163.4253.0](#) [25.190.2053.0](#) [25.194.3453.0](#)  
[25.320.4853.1](#) [25.320.5253.1](#) [25.325.3653.1](#) [25.326.3253.1](#) [25.326.3553.1](#) [25.330.1653.1](#) [25.330.4753.1](#) [25.330.5253.1](#) [25.334.3253.1](#)