



NOTE 1. APPLICABLE WIRE SIZE IS MENTIONED BELOW.

TABLE 1

CRIMP TYPE	APPLICABLE WIR		DIMENSIONS		
	WIRE SIZE	INSULATION OUTER DIA.	V GROOVE	φ A	φB
C 1	AWG# 8~10 (8 mml~5.5mml)	ø 7.25MAX.	WITH V GROOVE	4.3	5.6
C 2	AW9#10~12 (5.5mml~3.5mml)	ø 7.25MAX.	WITHOUT V GROOVE	3.5	4.5

						***	
3	RETAINER CLIP	1	SYNTHETIC RE	SIN			
2	SOCKET CONTACT	1	COPPER ALL	ΣY	SILV	ER PLATI	N G
1	SPRING	1	COPPER ALL	ΣY	SILV	ER PLATI	N G
ITEM	DESCRIPTION	Q 'TY	MATERIAL			FINISH	REMARKS
TOLERANCES ON :(INCHES)  FRACTIONS   DECIMALS   ANGLES   ANGLES   T. MORITA			CON (#8	T-JLD SOCKET ACHINE	5-08S-C* eference (CONTACT)	JAPAN JET ION CED HOVICS INDUSTRY, LTD. ONLY  MUSASHINO, AKISHIMA-SHI TOKYO, JAPAN DWG. NO.	
			M. Takagi	SERII	. 0 5	SCALE 2/1	SJ025431-E

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Standard Circular Contacts category:

Click to view products by JAE manufacturer:

Other Similar products are found below:

RC16M23J 133780-1 RM20M13D28 RM24M9D28 RMMX110-1D28 MS3474W10-6P L/C ELVP16100E 164-901-CD EN3545007SCE BV002BSQ20049CZ BV002SSQ160404CZ 1900ND05S1B00B 192900-0061 192900-0575 166566-1 1900ND04S1X00D 192900-0058 ST-JL05-16S-C3-100 ST-JL05-20S-C1-100 ST-JL05-20S-C2-100 T01-CRIMP-S03 APK-SA16A07-002 CONT-JL05-08S-C2-10 CONT-JL05-12S-C1-10 RC16M-23T RFD26L-1D28 BV002ASJ16049CW JN1-22-20S-R-PKG100 031-50565 SJS861301M ST-JL05-16S-C1-100 ST-JL05-20P-C1-100 82911466K 192991-0087 192900-0570 44-104-10003-02 T3P16FC3LZ ST-JL05-16S-C2-3500 ZP-4016-10NF CONT-JL05-12P-C1-10 RM20M12G8D28 031-50676 12115010110 RJFTVC2MG CAP-DACMDPC2 031-50675-002 CAP-DD1FDPC2 CAP-DACMDPC1 031-50966-010 ASSP-10-F-A-C-SA