



LY Series (2.0 mm Pitch 2 Row Crimp Connector)

2.0 mm Pitch 2 Row Crimp High-density Low-profile Connectors



High-density, low-profile connectors with 2.0 mm grid contact spacing. They are designed with vibration and full resistant locking mechanism.

[Catalog](#) [Specifications](#) [Handling Instructions](#) [Test Report](#) [Product Information Modules](#) [Applicable Tools](#) [Product Videos](#) [Product Samples](#) [Stock Search](#) [PDF Download](#) 

Features

- 2.0 mm pitch, Double row, Crimp, High-density, Low-profile connectors
- 8.0 mm mounted height (straight type) and 5.3 mm thickness
- Combination of box type pin header (straight and right angle) to be secure against breaking-down and twisting of contacts
- Cable socket housing (crimp termination type) enable ever higher density packaging of internal circuits in equipment

General Specifications

Number of Contacts	4, 6, 8, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 34, 36, 38, 40, 42, 44
---------------------------	---

Rated Current	3 A
Dielectric Withstanding Voltage	1000 VACr.m.s. (1 minute)
Insulation Resistance	1000 megohm min.
Contact Resistance	10 milliohm max.
Applicable Wire	#30 to #22 AWG
Operating Temperature Range	-40 deg. C to +85 deg. C
Circuit Board Thickness	1.6 mm

Notice

1. The values specified in this web site are only for reference. The products and their specifications are subject to change without notice. Contact our sales staff for further information before considering or ordering any of our products.
For purchase, a product specification must be agreed upon.
2. Users are requested to provide protection circuits and redundancy circuits to ensure safety of the equipment, and sufficiently review the suitability of JAE's products to the equipment.
3. The products presented in this web site are designed for the uses recommended below.
We strongly suggest you contact our sales staff when considering use of any of the products in any other way than the recommended

applications or for a specific use that requires an extremely high reliability.

(1) Applications that require consultation:

*Please contact us if you are considering use involving a quality assurance program that you specify or that is peculiar to the industry, such as:

Automotive electrical components, train control, telecommunications devices (mainline), traffic light control, electric power, combustion control, fire prevention or security systems, disaster evention equipment, etc.

*We may separately give you our support with a quality assurance program that

you specify, when you think of a use such as :

Aviation or space equipment, submarine repeaters, nuclear power control systems, medical equipment for life support, etc.

This site uses cookies to improve its performance, enhance your user experience and tailor advertising. By using this site you consent to the use of cookies as described in our usage policy unless you have changed your cookie settings. Please click [here](#) for more information.

Accept and Hide This Message

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [JAE](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)
[609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-010LF](#)
[65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5020](#) [707-](#)
[5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#) [FCN-360C032-B](#) [FCN-](#)
[367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)