MX80B04PZ1A

Product Details

Part Number	MX80B04PZ1A
Status	Active
Features	Compact Waterproof In-line Connectors for Automotive Applications, Pin connecter, 4 pos.
Number of Positions	4 pos.
Contact Pitch	2.54 mm
Rated Current (Ambient temperature: 105°C)	3.7A, when 0.35mm ² wire is used, 4.5A, when 0.5mm ² wire is used, 10A, when 1.0mm ² wire is used (Ambient temperature: 80°C)
Waterproof/ Non-waterproof	Waterproof
Applications	Automotive applications such as side view mirrors, number-plate light, and other applications requiring water-resistance.
Connector Type	Pin connecter
Number of Rows	1 row
Contact Type	Pin (Contacts are sold separately)
Wire Termination Style	-
Material of Insulator	PBT-GF10
Material of Contact	-
Finish of Contact in Connecting Area	-
Finish of Contact in Terminal Area	-

Documents	Catalog — PDF Download —
Stock Search	Stock Search >
RoHS compliant	10 substances (2011/65/EU)
REACH compliant	201 substances (16/07/2019)
Environment Information	
Combination	MX80A04SZ1A
Remarks	

Notice

- The values specified in this web site are only for reference. The
 products and their specifications are subject to change without notice.
 Contact our sales staff for further information before considering or
 ordering any of our products.
 - For purchase, a product specification must be agreed upon.
- Please contact us if you are considering use involving a quality
 assurance program that you specify or that is peculiar to the industry.
 Also contact us regarding the details of use, usage, specification
 before considering or ordering any of our products.
- 3. Users are requested to provide protection circuits and redundancy circuits to ensure safety of the equipment, and sufficiently review the suitability of JAE's products to the equipment.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Automotive Connectors category:

Click to view products by JAE manufacturer:

Other Similar products are found below:

003-018-000 60403001 60993906-B M902-2131 M902-2161 72.330.1035.1 73.353.4028.0 F119300-B F166900 F258300-B F358300-B F407400 F444110 F487000 F509500B-B 827153-1 8N1515-32-24P 9-1326729-8 925474-1 928905-1 964562-4 968782-1 GT17SA-8DS-HU 98891-1012 98947-1016 12004475-L 12010290 12010309-B 12015454 12020219-B 12020308 12041318-B 12052225-L 12052466 12059125 12064869 12004327-B 12010503-B 12015308 12015384 12015909 1-21030-1 12041254 12041318 12047946-B 12047957 12047957-L 12059473 12066261 12110546