


# High Voltage Ceramic Capacitor – JYC



## FEATURES

- Use for coupling, and by-pass circuit there are a stable and high reliability products.

## SPECIFICATIONS

Operating Condition Range	-25°C~ +85°C
Rated Working Voltage	1 KV – 15 KVDC
Capacitance Range	100pF – 10,000pF
Test Voltage	UR≤500V, U=2.5UR
	UR>500V≤6KV, U=1.5UR+500V
Dissipation Factor (tan δ)	UR>6KV≤15KV, U=1.5UR
	YL/SL/NPO: ≤0.5% max Y5P/Y5U/Y5V/Y5T: D.F. ≤2.5% max Y5R: D.F. ≤0.2% max
Insulation Resistance	YL/SL/NPO: ≥10GΩ
	Y5R/Y5P/Y5U/Y5V/Y5T: CR≤25nF, ≥4000MΩ CR>25nF, Rj•CR≥100s

Note: "s" for the time constant, that is, insulation resistance times the capacitance, in units of seconds, also known as megohm micro method.

RATED W. V	Y5P (±10%)	Y5U (±10%, ±20%)	Y5V (±20%)	SL (±10%)	N750 (±10%)	YL (±10%)	UJ (±10%)	DIMENSION			
								D	P	T	d
1KV	151~331	--	222	470	100	--	--	6.5	5.0	3.0	0.5
	471	--	272	560~680	150~330	--	--				
	681	--	332	101	--	--	--				
	102	--	--	--	--	--	--				
	122	821~102 (K)	472	--	--	--	--	7.5			
	--	102	--	--	--	--	--				
	--	122	--	--	--	--	--				
	--	152	--	--	--	--	--				
	--	222	--	--	--	--	--	8.5			
	--	272	682~103	--	--	--	--				
	--	332	--	--	--	--	--				
	--	472	--	--	--	--	--				
	--	152	--	--	--	--	--	9.5			
	222	--	--	--	--	--	--				
272	--	--	--	--	--	--					
332	--	--	--	--	--	--					
--	--	103	--	--	--	--	11.0				
--	103	--	--	--	--	--					
472	--	--	--	--	--	--					
--	--	--	--	--	--	--					
2KV	151~331	--	222	560~680	--	101	100	6.5	5.0	3.5	0.5
	471	--	--	--	--	--	150~330				
	681	102	272	470	--	--	--				
	--	122	332	--	--	--	--				
	--	152	--	--	--	--	--	7.5			
	102	--	--	--	--	--	--				
	--	821~102 (K)	472	--	--	--	--				
	--	222	--	--	--	--	--				
	122	--	--	--	--	--	--	9.5			
	152	--	--	--	--	--	--				
	--	--	--	--	--	--	--				
	--	272	--	--	--	--	--				
	--	332	--	--	--	--	--	10.5			
	--	472	--	--	--	--	--				
222	--	--	--	--	--	--					
--	--	682~103	--	--	--	--					
272	--	--	--	--	--	--	7.5				
332	--	--	--	--	--	--					

Please visit our website to get more update data, those data & specification are subject to change without notice.

# High Voltage Ceramic Capacitor – JYC

RATED W. V	Y5P (±10%)	Y5U (±10%, ±20%)	Y5V (+80-20%)	SL (±10%)	YL (±10%)	UJ (±10%)	DIMENSION				
							D	P	T	d	
3KV	101	--	--	180~220	680~820	100~150	6.5	7.5	4.0	0.5	
	151~331	--	--	--	--	--					
	471	--	--	--	--	--					
	--	--	102	--	--	--	--			7.5	0.55
	--	122	222	330~470	--	--					
	--	--	272	--	--	--	--				
	--	152	332	--	--	--	8.5				
	--	222	--	--	--	--	--				
	681	821~102 (K)	--	--	--	--	9.0				
	102	102	--	--	--	--	9.5				
	--	272	472	--	--	--	10.5				
	122	332	--	--	--	--	11.5				
	152	--	--	--	--	--	13.0				
	--	472	--	--	--	--	13.5				
	222	--	--	--	--	--	14.5				
--	--	682~103	--	--	--	--	0.6				
272	--	--	--	--	--	--					
332	--	--	--	--	--	--					
4KV	101	471 (K)	102	--	--	--	6.5	7.5	4.0	0.55	
	221	681 (K)	--	--	--	--					
	331	--	--	--	--	--					
	--	--	152	--	--	--	7.0				
	471	--	--	--	--	--	7.5				
	--	102	222	--	--	--	8.0				
	681	--	--	--	--	--	8.5				
	--	152	332	--	--	--	9.5				
	--	222	--	--	--	--	10.0				
	102	--	472	--	--	--	12.5				
	--	--	682	--	--	--	13.5				
--	--	103	--	--	--	10.0	0.6				
5KV	101	331 (K)	102	--	--	--		6.5	10.0	5.0	0.55
	221	--	--	--	--	--					
	331	681 (K)	152	--	--	--					
	--	102	--	--	--	--	7.5				
	471	--	222	--	--	--	8.5				
	--	471 (K)	--	--	--	--	9.5				
	681	--	--	--	--	--	10.5				
	--	152	332	--	--	--	11.0				
	--	222	--	--	--	--	11.5				
	--	--	472	--	--	--	12.0				
	102	--	--	--	--	--	--	0.6			
6KV	101	331 (K)	102	--	--	--	6.5		10.0	5.0	0.55
	221	471 (K)	--	--	--	--					
	331	681 (K)	152	--	--	--					
	--	102	--	--	--	--	7.5				
	471	--	--	--	--	--	8.5				
	--	--	222	--	--	--	9.5				
	681	--	--	--	--	--	10.5				
	--	152	--	--	--	--	11.0				
	--	--	332	--	--	--	11.5				
	102	222	--	--	--	--	12.0				
	--	--	472	--	--	--	--	0.6			

Please visit our website to get more update data, those data & specification are subject to change without notice.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [jb manufacturer](#):*

Other Similar products are found below :

[JFX02G225J000000B](#) [JSX-82U/250-5%](#) [JFX02E126J000000B](#) [JFX02G106J000000B](#) [JFX02E226J000000B](#) [JFX02E686J000000B](#)  
[JFX02E825J000000B](#) [JFX02G475J000000B](#) [JFX02E626J000000B](#) [JSX-68U/250-5%](#) [JFX02E107J000000B](#) [JFX02E167J000000B](#) [JSX-](#)  
[22U/250-5%](#) [JFX02G334J000000B](#) [JFX02G825J000000B](#) [JFX02G685J000000B](#) [JSX-100U/250-5%](#) [JSX-6.8U/250-5%](#)  
[JFX02E826J000000B](#) [JFX02G206J000000B](#) [JFX02E684J000000B](#) [JFX02E756J000000B](#) [JFX02E476J000000B](#) [JFX02E435J000000B](#) [JSX-](#)  
[33U/250-5%](#) [JFX02G155J000000B](#) [JFX02E474J000000B](#) [JFX02E566J000000B](#) [JFX02E405J000000B](#) [JFX02E475J000000B](#)  
[JFX02E166J000000B](#) [JFX02E506J000000B](#) [JFX02E755J000000B](#) [JYAA4331KDB075000B](#) [JSX-3.3U/250-5%](#) [JFX02E336J000000B](#)  
[JFX02E306J000000B](#) [JSX-8.2U/250-5%](#) [JSX-47U/250-5%](#) [JSX-5,6U/250-5%](#) [JFX02E186J000000B](#) [JFX02E334J000000B](#)  
[JFX02G166J000000B](#) [JFX02E416J000000B](#) [JFX02G126J000000B](#) [JFX02E276J000000B](#) [JFX02E156J000000B](#) [JFX02G156J000000B](#)  
[JFX02E565J000000B](#) [JFX02G186J000000B](#)