



# T210·T245·T470 SOLDERING HANDPIECES

# T210-T245-T470 / SOLDERING HANDPIECES

**T210-A** Green grip Micro Handpiece (1,5m cable) **T210-PA** Blue grip Micro handpiece

Use C210 cartridge range

#### ESD Safe

Connectable to CD, DI, DD, DDR, DM and RM

**T245-A** Green grip Handpiece (1,5m cable) **T245-PA** Blue grip Handpiece

Use C245 cartridge range

#### ESD Safe

Connectable to CD, DI, DD, DDR, DM, RM, HD and HDR

T245-NA Nitrogen Handpiece (Green Grip) with set screw (1,5m cable)

Use C245 cartridge range

KN Nitrogen Kit is needed

#### ESD Safe

Connectable to DI, DD, DDR, DM, RM.

T470-A Soft Touch Handpiece (Green grip) with set screw (1,5m cable)

T470-SA Soft Touch Handpiece (Green grip) with set screw (3m cable)

Use C245 and C470 cartridge range

### ESD Safe

Connectable to CD, DI, DD, DDR, DM, RM, HD and HDR

**T470-FA** Foamed Comfort Handpiece (Green grip) with set screw (1,5m cable)

T470-MA Foamed Comfort Handpiece (Green grip) with set crew (3m cable)

Use C245 and C470 cartridge range


# Not ESD Safe

Connectable to CD, DI, DD, DDR, DM, RM, HD and HDR

## CHANGING THE HANDPIECE'S CARTRIDGE



- 1. Place the handpiece in the extractor and remove the cartridge.
- 2. Place the handpiece on top of the new cartridge, press it slightly down and remove the handpiece from the extractor.




Press the cartridge into the opening A, B or C:

- A. For straight C210 cartridges.
- **B**. For curved C210 cartridges.
- C. For C245 cartridges.



# CHANGING THE HANDPIECE'S CARTRIDGE



# Important.

It is essential to insert the cartridge till the end for a good connection. Use the mark as reference.

# 

Untigh the screw before changing the cartridge and tight again once the cartridge is properly inserted. **T470** and **T245-NA** with set screw.

**WARNING:** It is esential to tighten this screw for the tool to function.

# **ACCESSORIES**

## **Fume extractor**

Specially designed for the JBC Series T210, T245 and T470 handpieces. Easily clips onto the handpiece and can be quickly removed for easy maintenance.



# **MAINTENANCE**

We recomend periodic cleaning of the metal ring and handpiece support using a solvent.

Due to the nature of its use, the handpiece has a limited life and may require replacing.



CC8200 Cable collector



# **TECHNICAL SPECIFICATIONS**

#### **HANDPIECES**

- T210-A Micro Handpiece.

For high precision work, SMD, etc.

- T210-PA Blue grip Micro Handpiece.

For accuracy soldering work and leaded jobs .

- T245-A Handpiece.

For general soldering work.

- T245-PA Blue handpiece.

For general soldering work and leaded jobs.

- T470-A / T470-SA Handpiece.

For heavy duty soldering applications.

- T470-FA / T470-MA Comfort Handpiece.

Thermally insulated for high thermal demand and prolonged heavy duty soldering applications.



This product should not be thrown in the garbage.



#### WARRANTY

JBC's 2 years warranty guarantees this equipment against all manufacturing defects, covering the replacement of defective parts and all necessary labour.

Warranty does not cover product wear due to use or mis-use.

In order for the warranty to be valid, equipment must be returned, postage paid, to the dealer where it was purchased enclosing this fully filled in, sheet.

SERIAL N°		
STAMP OF DEALER		
DATE OF PURCHASE		

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Soldering & Desoldering Stations category:

Click to view products by JBC Tools manufacturer:

Other Similar products are found below:

GS1116 T0053650699 BH-010 T0058768747 CA0202 CA0201 WXD2N T0058757898 T0058768743N T0051512199N T0058758721N
TS2300D WELPB102 0552406 CVC-7CN0004P CVC-8CH0010S CV-H5-DSHP 0016344 0019208 00B.SA.0 0120CDK 0352830
0460MDJ 0551903 0780550 0965970 0DIG20A45 0IC1100A 0ICV2000XV 0.SA.0 0T56 CL-SFE/1 FILTERS PX0410/03P/5055 RA150
35464 10G.SA.0 10LL4 3C.SA 3.TA AT850D/P TMT-HA300 TMT-PH200 TMT-PH300 5-048 5-050 5-051 5-052 5-054 5-057 5-107