

SMD 2012 KHZ RoHS:2.0








Features

- 2 pads surface mount package;
- Applications in mobile phone, Notebook and DSC;
- High reliable environmental performance;
- RoHS Compliant / Pb Free.

Crystals specifications

ITEMS(项目)	PARAMETER(规格说明) S21
Norminal Frequency	32.768 KHz
Load Capacitance(CL)	12.5 pF , other spec.
Series Resistance	90ΚΩ
Frequency Tolerance(at 25 ℃)	± 20 ppm , or specify
Frequency-Temperature coefficent	-0.04ppm/°C2
Operation Temperature Range	– 40 ~ + 85 °C
Storage Temperature Range	– 55 ~ +125 ℃
Shunt Capacitance (C0)	1.3pF typical
Motional Capacitance (C1)	6.4fF typical
Drive Level (DL)	0.5 μW Max.
Insulation Resistance (IR)	500 MΩ Min.
Aging (at 25 ℃)	± 3 ppm at first year
Packing Unit(包装单位)	3,000pcs/Reel

Dimensions



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Resonators category:

Click to view products by JGHC manufacturer:

Other Similar products are found below:

B39431R820H210 CSAC2.00MGCM-TC ECS-HFR-40.00-B-TR CSTLS4M00G53Z-A0 ZTB455E ECS-CR2-16.00-A-TR ECS-HFR-20.00-B-TR ECS-CR2-20.00-A-TR RO3164E-3 ASR418S2-T CSTNE10M0G520000R0 CSTLS8M00G53093-A0 CSTNE12M0G52A000R0 CSTLS18M4X54-A0 CSTLS16M9X53Z-B0 CSTLS24M0X51-A0 CSTLS25M0X51-B0 CSTLS18M0X51-B0 CSTLS4M00G53093-A0 CSTLS18M4X53-A0 CSTNE16M0V510000R0 CSTLS30M0X53-B0 CSTLS33M8X53-B0 CSTLS16M9X53-A0 CSTLS6M40G56-B0 CSTLS6M25G56-A0 CSTNE14M7V510000R0 CSTLS18M4X53-B0 CSTLS33M0X51-B0 CSTLS5M50G56-B0 7B008000101 7D038400101 TAXM24M2ILDBET2T TAXM26M2IHDBET2T 146-32.768-12.5-20-20/A 3225-24.00-12-10-10/A 7B009843M01 CF4016M00009T8188042 S32400001B0730D1JB X252016MLB4SI Q24FA20H00389 CSTLS16M0X54-B0 CSTLS4M19G56-B0 9AC04194152080D2JB CST3.58MGW CSTCR4M91G55B-R0 CSTLS3M68G56-B0 S2100327072090 FC-12M32.768KHZ9PF20PPM 7Y032768NW2