

SPECIFICATIONS

Rated(额定参数): 300V,8A
 Dielectric strength(抗电强度): AC1500V/1 Minute
 Insulation Resistance(绝缘电阻):1000MΩ Min
 Contact Resistance(接触电阻):20mΩ Max
 Wire Range(线径):1.6~28AWG
 Strip length(剥线长度):8~9mm
 Temp. range(操作温度): -40°C~+105°C
 MAX Soldering(瞬时温度):+250°C,5s



Housing Material(塑件): PA66 (UL94 V-0)
 Contact(端子): Phosphor Bronze, Tin plating(磷铜镀锡)

| PITCH RANGE | NOMINAL DIMENSION RANGE | | | | |
|-------------|-------------------------|-------|---------|--------|----------|
| | IN MM | IN MM | IN MM | IN MM | IN MM |
| TO 6 | OVER 6 | TO 10 | OVER 10 | TO 100 | OVER 100 |
| TO 10 | TO 10 | TO 24 | TO 30 | TO 60 | TO 100 |
| ±0.10 | ±0.15 | ±0.25 | ±0.30 | ±0.30 | ±0.50 |
| | | | | ±0.70 | ±1.00 |

Ordering Information

JL15EDGKD - 381 XX G X 1

Pitch
381=3.81PH
No.of pins
2P,3P,4P~24P
Housing Color
B=Black
G=Green
U=Blue
R=Red
W=White
Y=Yellow
O=Orange
E=Grey
Packing
O=Pe bog
T=Tube
A=Troy



| REV | DATE | MODIFICATION DESCRIPTION | CHANGE | OPERATION | DRAW | SCALE | FIT | PART NO. | TITLE: |
|-----|------------|--------------------------|--------|---|---------|-------|-----|--------------------|--|
| A0 | 2020.05.22 | NEW DRAWING | | X.XX ±0.20 X.XXX ±0.10 Angle ±3° | CHECK | A4 | 1/1 | JL15EDGKD-381XXGX1 | 3.81 Pitch Female Plugable Terminal Blocks |
| 1 | | | | DIM TOL | APPROVE | PROJ. | | | |

JILIN® 东莞市锦凌电子有限公司
 DONGGUAN JINLING ELECTRONIC CO.,LTD

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pluggable Terminal Blocks](#) category:

Click to view products by [JILN](#) manufacturer:

Other Similar products are found below :

[57.510.0053](#) [MC 1.5/ 6-ST-3.5 GY AU](#) [ET02015000J0G](#) [734-104](#) [734-302](#) [860505](#) [860516](#) [860810](#) [GBPACX-12](#) [93.731.4953.0](#) [PV05-5,08-K](#) [PVP03-3,50](#) [PVP04-3,50](#) [PVS02-5,00](#) [1-1986160-3](#) [1377680000](#) [1531000000](#) [1546228-5](#) [ELFP03110](#) [ELFT07250](#) [ELVD12100](#) [ELVF09400](#) [ELVP03100](#) [ELXH071G0E](#) [1700410](#) [1702246](#) [1705229](#) [1714537](#) [1717806](#) [1719600](#) [1728941](#) [1734692](#) [1734795](#) [1740291](#) [1740628](#) [1746952](#) [1750207](#) [1752865](#) [1754115](#) [1754144](#) [1756913](#) [1760051](#) [1760336](#) [1765111](#) [1776388](#) [1777701](#) [1783410](#) [1800227](#) [1801080](#) [1809474](#)