

NOTES1:

- UL Standard
- 1. Rated voltage/current : 300V / 41A
- 2. Withstanding voltage : AC1600V/1Min.

IEC Standard

1. Pollution degree	2	2	3
Overvoltage category	II	III	III
Rate impulse voltage(KV)	6KV	6KV	6KV
Rate voltage(V)	1000V	630V	630V
Rate current(A)		41A	630V

NOTES2:

- 1. Dimension shall be interpreted per ASME Y14.5-2009
- 2. Pitch : 7.62mm, Poles : N=02~12P
- 3. Operating temperature : -40°C~+105°C
- 4. Undimensioned tolerances:






Pitch range in mm	Nominal dimension range in mm			Tolerance
	Over	TO	Under	
6	TO	30	TO	0.1/10
10	TO	60	TO	≤
24	TO	100	TO	≤
30	TO	150	TO	≤
±0.15±0.20±0.30±0.50±0.70±1.00±1.30 ±2'				

5. RoHS Compliance

Ordering Information

JL5EDGRHM-762 XX G 0 1

Pitch 762=7.62PH
 No. of pins 2P, 3P, 4P~12P
 Housing Color B=Black, G=Green, U=Blue, R=Red, V=White, Y=Yellow, D=Orange, E=Grey
 Packing 0=Pe, bag, T=Tube, A=Tray



REVISION RECORD			
REV	ECN	DESCRIPTION	DATE
A0		NEW	20.12.02

DRAW	SHUANGPING ZHENG		SCALE	FIT	PART NO.	JL5EDGRHM-762XXG01
	UNIT	mm				
CHECK	LICHAD LIU		SIZE	SHEET	TITLE:	JL5EDGRHM-762-XXP 插拔式公座/带耳/绿色/弯脚
	APPROVE	YONGLIANG GAO				
PRD	1/1					

JILIN 东莞市锦凌电子有限公司
 DONGGUAN JINLING ELECTRONIC CO., LTD

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pluggable Terminal Blocks](#) category:

Click to view products by [JILN](#) manufacturer:

Other Similar products are found below :

[57.510.0053](#) [MC 1.5/ 6-ST-3.5 GY AU](#) [ET02015000J0G](#) [734-104](#) [734-302](#) [860505](#) [860516](#) [860810](#) [GBPACX-12](#) [93.731.4953.0](#) [PV05-5,08-K](#) [PVP03-3,50](#) [PVP04-3,50](#) [PVS02-5,00](#) [1-1986160-3](#) [1377680000](#) [1531000000](#) [1546228-5](#) [ELFP03110](#) [ELFT07250](#) [ELVD12100](#) [ELVF09400](#) [ELVP03100](#) [ELXH071G0E](#) [1700410](#) [1702246](#) [1705229](#) [1714537](#) [1717806](#) [1719600](#) [1728941](#) [1734692](#) [1734795](#) [1740291](#) [1740628](#) [1746952](#) [1750207](#) [1752865](#) [1754115](#) [1754144](#) [1756913](#) [1760051](#) [1760336](#) [1765111](#) [1776388](#) [1777701](#) [1783410](#) [1800227](#) [1801080](#) [1809474](#)