



RECOMMAND P. C. B LAYOUT
TOLERANCE: ± 0.10

NOTES:

1. MATERIAL SPECIFICATION:
 - 1) INSULATION MATERIAL: THERMOPLASTIC HALGENFREI.
 - 2) SHELL: SPCC T: 0.30mm
 - 3) TERMINAL: COPPER ALLOY T: 0.25mm
- PLATING: NICKEL
- PLATING: GOLD/TIN PLATED;
2. ELECTRICAL CHARACTERISTIC:
 - 1) INSULATION RESISTANCE: 100M Ω MIN;
 - 2) CONTACT RESISTANCE: 30m Ω MAX;
 - 3) WITHSTANDING VOLTAGE: 500V AC;
3. MECHANICAL CHARACTERISTICS:
 - 1) INSERTION FORCE: 3.57kgf Max;
 - 2) EXTRACTION FORCE: 1.02kgf Min;

产品图
PRODUCT CHART DWG

公差一按表
TOLERANCE UNLESS OTHERWISE

XXX	± 0.10	.XXX	± 0.5
.XX	± 0.15	.XX	$\pm 1.$
X	± 0.25	X	$\pm 2.$
X	± 0.30	X	$\pm 5.$

DATE	2019.11.23
SCALE	1:1
UNITS	MM

APPD	核准	黄国荣
CHKD	审核	郭志富
DRAWING	制图	YANG

VIEW	角法
PRODUCT NO.	AF 180度插板 5P
PRODUCT PART NO.	



版本
VER

A0

深圳市精拓金电子有限公司

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [Jing](#) manufacturer:

Other Similar products are found below :

[10033527-N3112MLF](#) [17-210561](#) [GMCB05B11124H1EU](#) [17-200931](#) [65-647-8-BK-BU](#) [690-010-295-484](#) [73725-1191BLF](#) [950](#) [E8144-B01021-L](#) [A-USB A-LP-SMT-C](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBB15131](#) [MUSBC111M5](#) [MUSBD11135](#) [217450-1](#) [CA 6 W LD](#) [896-30-004-00-000000](#) [KUSBVX-BS1N-W30](#) [KUSBX-AP-KIT-SCBLK](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W](#) [KUSBX-SMTAS1NBTR](#) [KUSBX-SMTBS1NBTR](#) [30-498-6](#) [SK-60A-2](#) [17-200261](#) [17-210051](#) [1734082-1](#) [FK-37-32SL](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [30-9503](#) [M9177/2-1](#) [MAB 5 S](#) [MIKROE-1451](#) [33UBBR-04SW11R](#) [USBFTV2PEM2G](#) [USBFTVC6ZN](#) [USBFTVSCCG](#) [KUSBX-AS2N-W30](#) [KUSBX-SLAS1N-W](#) [KUSBX-SLAS1N-W30](#) [1-1734084-2](#) [E8110-001-01](#) [MUSBC11135](#) [NK-27-32SL](#)