







目錄 MAPX	投交內容 MODIFICATION	日期 DATE
------------	----------------------	------------



NOTE2:

DIM	ALDIM	BI	PART No.
T.50	6.80	T04-006RT138RT1R	
L.50	6.80	T04-006RT138RT1R	
1.00	6.50	T04-006RT138RT1R	
1.50	6.50	T04-006RT138RT1R	
1.00	5.50	T04-006RT138RT1R	
1.50	5.50	T04-006RT138RT1R	
1.00	5.00	T04-006RT140RT1R	
1.50	5.00	T04-006RT141RT1R	

- NOTE:
- MATERIAL SPECIFICATION:
 - HOUSING: HIGH TEMPERATURE RESISTANT PLASTIC: UL94 V-0.
 - CONTACTS: COPPER ALLOY
 - MID PLATE: STAINLESS STEEL
 - FRONT SHELL: STAINLESS STEEL
 - PLATING SPECIFICATION:
 - CONTACTS:
 - 50μ" MIN. UNDER PLATED OVER ALL.
 - 50μ" MIN. UNDER PLATED OVER ALL.
 - PLATING THICKNESS FOLLOW THE P/N (GOLD PLATING THICKNESS FOLLOW THE P/N)
 - FRONT SHELL:
 - 30μ" MIN. UNDER PLATED OVER ALL.
 - MID PLATE:
 - 30μ" MIN. UNDER PLATED OVER ALL.
 - MATERIAL PERFORMANCE:
 - INSERTION FORCE: 0.5~2.0kgf.
 - REMOVAL FORCE: 0.8kgf~2.0kgf.
 - DURABILITY: 2000 CYCLES.
 - ELECTRICAL PERFORMANCE:
 - CURRENT RATING: 5.0A
 - VOLTAGE RATING: 5.0V
 - LCOR:
 - VBUS & GND PINS AND OTHER PINS: 40mΩ /PIN MAX.
 - SHIELD: 50mΩ /MAX.
 - LCOR MAX. CHANGE OF ALL PINS: 10mΩ.
 - INSULATION RESISTANCE: 100MΩ MIN
 - DIELECTRIC WITHSTAND VOLTAGE, AC 100V FOR 1 MINUTE.
 - ENVIRONMENTAL PERFORMANCE:
 - OPERATING TEMPERATURE: -25° C~+85° C.
 - IR REFLOW:
 - THE PEAK TEMPERATURE ON THE BOARD SHALL BE MAINTAINED FOR 10 SECONDS AT 260° C.

深圳市精拓金电子有限公司

产品图

PRODUCT CHART DWG

公差一览表

TOLERANCE	UNLESS OTHERWISE
X	±0.25
.X	±0.20
.XX	±0.15
.XXX	±0.10

单位 UNITS	MM
比例 SCALE	1:1
日期 DATE	2015/10/20
制图 DRAWING	林属升
审核 CHKD	郭志富
核准 APPD	黄国荣
产品料号 Product Part No.	918-418K2028140001
产品名称 Product No.	TYPE-C3.1母座两脚立式插板6.5不锈钢
角法	LCF 黑胶 6PIN/SY
版本 VER	A0

您正在使用 ZWCAD 2022 个人版, 不得用于商业用途, 详情请咨询40077482-588。

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [Jing](#) manufacturer:

Other Similar products are found below :

[950](#) [A-USB A-LP-SMT-C](#) [A-USB B-TOP-C](#) [MUSBD11135](#) [17-200721](#) [217450-1](#) [KMBVX-TH-5S-B30](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W30](#) [935](#) [957](#) [30-498-6](#) [SK-60A-2](#) [1734082-1](#) [30-470](#) [30-489](#) [30-541](#) [MAB 5 S](#) [A-USB A-2P-C](#) [MIKROE-1451](#)
[USBFTVSCCG](#) [1-1734084-2](#) [MUSBA81130](#) [NK-27-32SL](#) [NK-L8-22C-5/8](#) [10135326-001LF](#) [4198](#) [690-024-633-031](#) [UB-20PMFP-LC7001](#)
[17-200011](#) [UB-20AFMM-LL7A01](#) [CAP-WCCMLPB1](#) [CAP-WCCMLPC1](#) [2274475-3](#) [914-614A2025S10200](#) [USB3FTV7SAGF059](#)
[USB3FTV2SAZNF459](#) [USB3FTV7SAZNF459](#) [HYCW153-USBD05-500B](#) [HYCW219-USBD05-075B](#) [HYCW148-USBD05-117B](#)
[HYCW149-USBD05-740B](#) [HYCW204-USBD05-108B](#) [HYCW214-USBA04-113B](#) [HYCW213-USBA04-113B](#) [KMMX-BSMT35S-1-B30TR](#)
[2345986-1](#) [10082141-N340LF](#) [10117836-011LF](#) [GSB3C3133DSYHR](#)