



DRAWN		CHECKED		APPROVED		TOLERANCE		3rd ANGLE PROJECTION	
TITLE		USB AM 大电流焊线式		TITL		UNIT		mm	
PART NO.		DRAWING NO.		SCALE		SHEET		REV.	
1:1		1 OF 1		A4		X1			

深圳市精拓金电子有限公司

Note:

- Material:
- 1.1,Housing: High temperature thermoplastic with/black g.f,UL94v-0
- 1.2,Contact: copper alloy,t=0.25mm
- 1.3,Shell: copper/Ferroalloy alloy,t=0.35mm
- 2.Specification:
 - 2.1,Current rating:3A Max.
 - 2.2,Dielectric withstanding voltage: 100 V(ac) for 1 min.
 - 2.3,Contact resistance: 30 mΩ Max.
 - 2.4,Insulation resistance: 100 MΩ Min.
 - 2.5,Total mating force: 3.57 Kgf Max.
 - 2.6,Total unmating force: 1.0 Kgf Min.
- 3.Finish:
 - 3.1,Contact: Plated Gold in Mating Area
 - Tin On Solder Tails
 - Shell: Nickel Plating
- 4.Environmental:
 - 4.1,Temperature range: -55°C~85°C

REVISIONS			
SYM	Ecn No.	MODIFICATION	DATE
ISSUED			

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [Jing](#) manufacturer:

Other Similar products are found below :

[10033527-N3112MLF](#) [17-210561](#) [GMCB05B11124H1EU](#) [17-200931](#) [65-647-8-BK-BU](#) [690-010-295-484](#) [73725-1191BLF](#) [950](#) [E8144-B01021-L](#) [A-USB A-LP-SMT-C](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBB15131](#) [MUSBC111M5](#) [MUSBD11135](#) [217450-1](#) [CA 6 W LD](#) [896-30-004-00-000000](#) [KUSBVX-BS1N-W30](#) [KUSBX-AP-KIT-SCBLK](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W](#) [KUSBX-SMTAS1NBTR](#) [KUSBX-SMTBS1NBTR](#) [30-498-6](#) [SK-60A-2](#) [17-200261](#) [17-210051](#) [1734082-1](#) [FK-37-32SL](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [30-9503](#) [M9177/2-1](#) [MAB 5 S](#) [MIKROE-1451](#) [33UBBR-04SW11R](#) [USBFTV2PEM2G](#) [USBFTVC6ZN](#) [USBFTVSCCG](#) [KUSBX-AS2N-W30](#) [KUSBX-SLAS1N-W](#) [KUSBX-SLAS1N-W30](#) [1-1734084-2](#) [E8110-001-01](#) [MUSBC11135](#) [NK-27-32SL](#)