


NOTE:
 RATING
 *VOLTAGE RATING: 30V AC (Rms)
 *CURRENT RATING: 1.5A MAX
 ELECTRICAL CHARACTERISTICS
 *CONTACT RESISTANCE: 30mΩ MAX
 *INSULATION RESISTANCE: 1000MΩ MIN
 *DIELECTRIC WITHSTANDING VOLTAGE: 500V AC AT 1minute

MATERIALS
 *TERMINAL: Brass Plating Nickel before Plating Gold Tin.
 *HOUSING: PBT.
 *SHELL: Brass & SPCC Plating Nickel.
 *TERMINALS: Gold Plating : G/F 3U" 5U" 10" 15U" 30U" 50U"
 *PART MUST COMPLY ZYZ ROHS SPECIFICATION.



SUGGESTED PCB LAYOUT
 GENERAL TOLERANCE: ± 0.05

D		修改外壳侧面弹片	2012. 05. 19
C		修改外壳脚尺寸	2011. 11. 20
B		修改PCB LAYOUT尺寸	2011. 07. 26
REV.	ECN NO.	LOCATION	DATE

品名ARTICLE: USB-A 母 90° 侧立直插式(新) 料号P/N:			
设计DES: D:	日期DATE	单位UNIT: MM	版本REV: D
审核CHK: D:	日期DATE	英码SHEET: 1/1	比例SCALE: N/A
批准: APV: D:	日期DATE	材质MATERIAL:	
		表面处理FINISHING:	
		图号MODEL:	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [Jing](#) manufacturer:

Other Similar products are found below :

[10033527-N3112MLF](#) [17-210561](#) [GMCB05B11124H1EU](#) [17-200931](#) [65-647-8-BK-BU](#) [690-010-295-484](#) [73725-1191BLF](#) [950](#) [E8144-B01021-L](#) [A-USB A-LP-SMT-C](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBB15131](#) [MUSBC111M5](#) [MUSBD11135](#) [217450-1](#) [CA 6 W LD](#)
[896-30-004-00-000000](#) [KUSBVX-BS1N-W30](#) [KUSBX-AP-KIT-SCBLK](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W](#) [KUSBX-SMTAS1NBTR](#) [KUSBX-SMTBS1NBTR](#) [30-498-6](#) [SK-60A-2](#) [17-200261](#) [17-210051](#) [1734082-1](#) [FK-37-32SL](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [30-9503](#) [M9177/2-1](#) [MAB 5 S](#) [MIKROE-1451](#) [33UBBR-04SW11R](#) [USBFTV2PEM2G](#) [USBFTVC6ZN](#) [USBFTVSCCG](#)
[KUSBX-AS2N-W30](#) [KUSBX-SLAS1N-W](#) [KUSBX-SLAS1N-W30](#) [1-1734084-2](#) [E8110-001-01](#) [MUSBC11135](#) [NK-27-32SL](#)