



PCB LAYOUT

备注：侧弹分为外弹与内弹

NOTES:
 Housing: Thermoplastics
 Contact: Copper Alloy
 Shell: Copper Alloy/Steel
 Voltage Current Rating: 1.5 AMP, 30V AC
 Insulation Resistance: 100M Ω Min.
 Contact Resistance: 30 M Ω Max.
 Dielectric Withstanding Voltage: 500W AC
 Temperature Range: -35 $^{\circ}$ C to +85 $^{\circ}$ C
 Insulator color: Black/White
 Plastic material: PB/LCP/Others
 Shell finish: Nickel plated/Tin-Lead plated
 Mechanical:
 Mating Force: 3.5KG MAX
 Umating Force: 0.7 KG MIN.
 Contact finish:
 01: Selective Gold Flash
 02: Selective Gold 3U
 03: Selective Gold 5U
 04: Selective Gold 15U
 05: Selective Gold 30U

| | | |
|------|--------------|------|
| 日期 | 变更内容 | 目錄 |
| DATE | MODIFICATION | MAPX |

| | | | | | | | | | | | |
|-------------------|-------|------------|-------|----------------------------|-------|------------|-----|------|-------|------------|------------------|
| 产品图 | | 公差一览表 | | TOLERANCE UNLESS OTHERWISE | | UNIT | MM | 制图 | Z-Y-B | 产品料号 | PRODUCT PART NO. |
| PRODUCT CHART DWG | | 公差一览表 | | TOLERANCE UNLESS OTHERWISE | | UNIT | MM | 制图 | Z-Y-B | 产品料号 | PRODUCT PART NO. |
| X | ±0.25 | X: | ±2' | X | ±2' | SCALE | 1:1 | 审核 | | 产品名称 | PRODUCT NO. |
| .XX | ±0.15 | .XX: | ±1' | X | ±0.20 | 比例 | 1:1 | 审核 | | 产品名称 | PRODUCT NO. |
| .XXX | ±0.10 | .XXX: | ±1' | X | ±0.20 | 比例 | 1:1 | 审核 | | 产品名称 | PRODUCT NO. |
| .XXX | ±0.10 | .XXX: | ±0.5' | X | ±0.25 | 比例 | 1:1 | 审核 | | 产品名称 | PRODUCT NO. |
| 日期 | | 2014/10/20 | | 日期 | | 2014/10/20 | | 日期 | | 2014/10/20 | |
| APPD | | 核准 | | APPD | | 核准 | | APPD | | 核准 | |
| 角法 | | 角法 | | 角法 | | 角法 | | 角法 | | 角法 | |
| 版本 | | 版本 | | 版本 | | 版本 | | 版本 | | 版本 | |
| A0 | | A0 | | A0 | | A0 | | A0 | | A0 | |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [Jing](#) manufacturer:

Other Similar products are found below :

[10033527-N3112MLF](#) [17-210561](#) [GMCB05B11124H1EU](#) [17-200931](#) [65-647-8-BK-BU](#) [690-010-295-484](#) [73725-1191BLF](#) [950](#) [E8144-B01021-L](#) [A-USB A-LP-SMT-C](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBB15131](#) [MUSBC111M5](#) [MUSBD11135](#) [217450-1](#) [CA 6 W LD](#)
[896-30-004-00-000000](#) [KUSBVX-BS1N-W30](#) [KUSBX-AP-KIT-SCBLK](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W](#) [KUSBX-SMTAS1NBTR](#) [KUSBX-SMTBS1NBTR](#) [30-498-6](#) [SK-60A-2](#) [17-200261](#) [17-210051](#) [1734082-1](#) [FK-37-32SL](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [30-9503](#) [M9177/2-1](#) [MAB 5 S](#) [MIKROE-1451](#) [33UBBR-04SW11R](#) [USBFTV2PEM2G](#) [USBFTVC6ZN](#) [USBFTVSCCG](#)
[KUSBX-AS2N-W30](#) [KUSBX-SLAS1N-W](#) [KUSBX-SLAS1N-W30](#) [1-1734084-2](#) [E8110-001-01](#) [MUSBC11135](#) [NK-27-32SL](#)