



RECOMMENDED PCB

规格: Specifications:
 电器: Electrical:
 接触阻抗: Contact Resistance
 50 milliohms MAX
 耐电压: Dielectric Withstanding Voltage:
 100 V AC AT Sea Level
 绝缘阻抗: Insulation Resistance:
 100 MEGA ohms MIN

材料: Material:
 塑胶: Housing: Ulting Temperature Thermoplastics,
 UL 94V-0 耐高温塑胶
 端子: Contact: Copper Alloy 铜合金
 外壳: Shell: Copper Alloy 铜合金
 电镀: Finish:
 外壳: Shell: Nickel/Plating 镀镍
 端子: Contact: Plated gold in Mating Area;
 Tin On Solder Tails
 接触点镀金, 脚镀锡

Ordering Informating
 X - 5 - XX

Contact plating
 01-Gold Flash
 02-5μ"Gold/ Tin
 03-15μ"Gold/ Tin
 04-30μ"Gold/Tin
 Plastic Color
 A=Black
 尺寸未注公差参考 ± 0.10

产品图
 PRODUCT CHART DWG

公差一览表
 TOLERANCE UNLESS OTHERWISE

X	±0.25	X'	±5'
X	±0.20	X'	±2'
.XX	±0.15	.XX'	±1'
.XXX	±0.10	.XXX'	±0.5'

单位 UNITS	MM	制图 DRAWING	Z-Y-B	产品料号 PRODUCT PART NO.	
比例 SCALE	1:1	审核 CHECK		产品名称 PRODUCT NAME	MINI 5P 母头 SMT
日期 DATE	2009/10/20	核准 APPD		角法 VIEW	
				版本 VER	A0

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [Jing](#) manufacturer:

Other Similar products are found below :

[10033527-N3112MLF](#) [17-210561](#) [GMCB05B11124H1EU](#) [17-200931](#) [65-647-8-BK-BU](#) [690-010-295-484](#) [73725-1191BLF](#) [950](#) [E8144-B01021-L](#) [A-USB A-LP-SMT-C](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBB15131](#) [MUSBC111M5](#) [MUSBD11135](#) [217450-1](#) [CA 6 W LD](#) [896-30-004-00-000000](#) [KUSBVX-BS1N-W30](#) [KUSBX-AP-KIT-SCBLK](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W](#) [KUSBX-SMTAS1NBTR](#) [KUSBX-SMTBS1NBTR](#) [30-498-6](#) [SK-60A-2](#) [17-200261](#) [17-210051](#) [1734082-1](#) [FK-37-32SL](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [30-9503](#) [M9177/2-1](#) [MAB 5 S](#) [MIKROE-1451](#) [33UBBR-04SW11R](#) [USBFTV2PEM2G](#) [USBFTVC6ZN](#) [USBFTVSCCG](#) [KUSBX-AS2N-W30](#) [KUSBX-SLAS1N-W](#) [KUSBX-SLAS1N-W30](#) [1-1734084-2](#) [E8110-001-01](#) [MUSBC11135](#) [NK-27-32SL](#)