



项目	零件名称	数量	材质	处理/备注
1	SHELL	1	STAINLESS	Ni:50u" (Black)
2	Molding HOUSING	2	L.C.P	(Black)
3	GND SPRING	2	STAINLESS	Ni:50u" (Black)
4	Insert molding 12PIN	2	L.C.P	Contact area: gold flash, Solder tails: Tn100u", Ni:50u"
5	CONTACT	24	COPPER ALLOY	
6	PCB	1		

**: SPECIFICATION**

**MATERIAL**

See drawing

**STANDARD DATA**

Operating temperature: -10°C ~ +60°C

Storage temperature: -20°C ~ +85°C

**ELECTRICAL**

Insulator resistance: 100Mohms Min.

Withstanding voltage: 100 VAC / minute

Contact resistance: initial 40mohms Max; after 50mohms Max.

**MECHANICAL**

Mating force: 5~20N

Umating force: 8~20N

Durability: 5000 cycles Min.

**产品图**  
PRODUCT CHART DWG

**公差一览表**  
TOLERANCE UNLESS OTHERWISE

公差	单位	MM	制图	产品料号	角法	版本
X ±0.25	UNIT	MM	Z-Y-B	PRODUCT PART NO.	USP-3.1 公头/双面POP板转micro无边	A0
X ±0.20	SCALE	1:1	审核	产品名称		
XX ±0.15	SCALE	1:1	核准	郭治富		
.XXX ±0.10	DATE	2015.07.14	APPD			

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [USB Connectors](#) category:*

*Click to view products by [Jing](#) manufacturer:*

Other Similar products are found below :

[10033527-N3112MLF](#) [17-210561](#) [GMCB05B11124H1EU](#) [17-200931](#) [65-647-8-BK-BU](#) [690-010-295-484](#) [73725-1191BLF](#) [950](#) [E8144-B01021-L](#) [A-USB A-LP-SMT-C](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBB15131](#) [MUSBC111M5](#) [MUSBD11135](#) [217450-1](#) [CA 6 W LD](#) [896-30-004-00-000000](#) [KUSBVX-BS1N-W30](#) [KUSBX-AP-KIT-SCBLK](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W](#) [KUSBX-SMTAS1NBTR](#) [KUSBX-SMTBS1NBTR](#) [30-498-6](#) [SK-60A-2](#) [17-200261](#) [17-210051](#) [1734082-1](#) [FK-37-32SL](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [30-9503](#) [M9177/2-1](#) [MAB 5 S](#) [MIKROE-1451](#) [33UBBR-04SW11R](#) [USBFTV2PEM2G](#) [USBFTVC6ZN](#) [USBFTVSCCG](#) [KUSBX-AS2N-W30](#) [KUSBX-SLAS1N-W](#) [KUSBX-SLAS1N-W30](#) [1-1734084-2](#) [E8110-001-01](#) [MUSBC11135](#) [NK-27-32SL](#)