



10A, 650V N-CHANNEL POWER MOSFET

Description

The F10N65L is a high voltage power MOSFET and is designed to have better characteristics, such as fast switching time, low gate charge, low on-state resistance and have a high rugged avalanche characteristics. This power MOSFET is usually used at high speed switching applications in switching power supplies and adaptors.


Features

- $R_{DS(ON)} < 1.0 \Omega$ @ $V_{GS}=10V$, $I_D=5.0A$
- Fast switching capability
- 100% Avalanche tested
- 100% ΔV_{DS} tested

Mechanical data

- Case: TO-220F-3L
- Approx. Weight: 1.767g (0.062oz)
- Lead free finish, RoHS compliant
- Case Material: "Green" molding compound, UL flammability classification 94V-0, "Halogen-free".

TO-220F-3L(*Prefix :F)



Absolute Maximum Ratings (Ta=25°C, Unless Otherwise Specified)

Parameter	Symbols	Ratings	Units
Drain-Source Voltage	V_{DSS}	650	V
Gate-Source Voltage	V_{GSS}	± 30	V
Continuous Drain Current $T_c=25^\circ C$ $T_c=100^\circ C$	I_D	10 6.3	A
Pulsed Drain Current (Note 2)	I_{DM}	40	A
Avalanche Energy Single Pulsed (Note 3)	E_{AS}	500	mJ
Power Dissipation ($T_c = 25^\circ C$)	P_D	65	W
Operating junction and storage temperature	T_J, T_{STG}	-55 ~ +150	$^\circ C$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.
Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating: Pulse width limited by maximum junction temperature.

3. L = 10mH, IAS = 10A, VDD = 50V, RG = 25 Ω , Starting $T_J = 25^\circ C$

Thermal Resistance

Parameter	Symbols	Ratings	Units
Thermal resistance, junction – case.	R_{thJC}	4	$^\circ C/W$
Thermal resistance, junction – ambient(min. footprint)	R_{thJA}	63	$^\circ C/W$



Electrical Characteristics (Ta=25°C, Unless Otherwise Specified)



Parameter	Symbols	Test Conditions	Min	Typ	Max	Units
Off Characteristics						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250μA	650			V
Drain-Source Leakage Current	I _{DSS}	V _{DS} =650V, V _{GS} =0V			1.0	uA
Gate- Source Leakage Current	Forward	I _{GSS}	V _{GS} =30V, V _{DS} =0V		100	nA
	Reverse		V _{GS} =-30V, V _{DS} =0V		-100	
On Characteristics						
Gate Threshold Voltage	V _{GS(TH)}	V _{DS} =V _{GS} , I _D =250μA	2.0		4.0	V
Static Drain-Source On-State Resistance	R _{D(S)ON}	V _{GS} =10V, I _D =5.0A		0.77	1.0	Ω
Transconductance	g _{fs}	V _{DS} =15V, I _D =2A		4.8		S
Dynamic Characteristics						
Input Capacitance	C _{ISS}	V _{DS} =15V, V _{GS} =0V, f=1.0MHz		1601		pF
Output Capacitance	C _{OSS}			137		pF
Reverse Transfer Capacitance	C _{rss}			11		pF
Gate resistance	R _G			2.7		Ω
Switching Characteristics						
Total Gate Charge (Note 1)	Q _G	V _{DS} =520V, V _{GS} =10V, I _D =10A (NOTE1,2)		35		nC
Gate-Source Charge	Q _{GS}			7		nC
Gate-Drain Charge	Q _{GD}			18		nC
Turn-On Delay Time (Note 1)	t _{D(ON)}	V _{DS} =325V, V _{GS} =10V, R _G =25Ω, I _D =10A (NOTE1,2)		23		ns
Turn-On Rise Time	t _R			15		ns
Turn-Off Delay Time	t _{D(OFF)}			90		ns
Turn-Off Fall Time	t _F			30		ns
Drain-source Diode Characteristics And Maximum Ratings						
Maximum Body-Diode Continuous Current	I _S				10	A
Maximum Body-Diode Pulsed Current	I _{SM}				40	A
Drain-Source Diode Forward Voltage (Note 1)	V _{SD}	I _{SD} =10A, V _{GS} =0V			1.4	V
Reverse Recovery Time (Note 1)	t _{rr}	I _F =10A, V _{GS} =0V di/dt=100A/us		320		ns
Reverse Recovery Charge	Q _{rr}			4.2		uC

Notes:

1. Pulse Test: Pulse width ≤ 300μs, Duty cycle ≤ 2%.
2. Essentially independent of operating temperature.




Test Circuits and waveforms







Test Circuits and waveforms




Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Gate Charge Waveform



Unclamped Inductive Switching Test Circuit



Unclamped Inductive Switching Waveforms



Typical Characteristics

Fig.1 Output characteristics




Fig.2 Power Dissipation




Fig.3 Drain Current Derating




Fig.4 Drain-Source On-Resistance vs. Drain Current




Fig.5 Gate Threshold Voltage vs. Junction Temperature




Fig.6 Body-diode Forward Characteristics




Fig.7 Drain-Source On-Resistance vs. Junction Temperature





Fig.8 Breakdown Voltage vs. Junction Temperature





Typical Characteristics

Fig.9 Capacitance Characteristics




Fig.10 Gate Charge Characteristics




Fig.11 Safe Operating Area






Fig.12 Max. Transient Thermal Impedance






Package Outline
Through Hole Package ; 3 leads

TO-220F-3L



Marking Diagram



- Unmarkable Surfacea
- Marking Composition Field
- a:Ejector Pin Mark
- A:Marking Area
- B: Lot Code
- C: Additional Information
- D:Date Code (YWW)
- Y:Years(0~9)
- WW:Week



Important Notice and Disclaimer

Jingdao Microelectronics reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

Jingdao Microelectronics makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Jingdao Microelectronics assume any liability for application assistance or customer product design.

Jingdao Microelectronics does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of Jingdao Microelectronics.

Jingdao Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of Jingdao Microelectronics.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for MOSFET category:

Click to view products by Jingdao manufacturer:

Other Similar products are found below :

[IRFD120](#) [JANTX2N5237](#) [BUK455-60A/B](#) [MIC4420CM-TR](#) [VN1206L](#) [NDP4060](#) [SI4482DY](#) [IPS70R2K0CEAKMA1](#) [SQD23N06-31L-GE3](#)
[TK16J60W,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#) [DMN1017UCP3-7](#) [DMN1053UCP4-7](#) [SQJ469EP-T1-GE3](#) [NTE2384](#) [DMC2700UDMQ-7](#)
[DMN2080UCB4-7](#) [DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [DMP22D4UFO-7B](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#)
[STF5N65M6](#) [IRF40H233XTMA1](#) [STU5N65M6](#) [DMN6022SSD-13](#) [DMN13M9UCA6-7](#) [DMTH10H4M6SPS-13](#) [DMN2990UFB-7B](#)
[IPB80P04P405ATMA2](#) [2N7002W-G](#) [MCAC30N06Y-TP](#) [MCQ7328-TP](#) [NTMC083NP10M5L](#) [BXP7N65D](#) [BXP4N65F](#) [AOL1454G](#)
[WMJ80N60C4](#) [BXP2N20L](#) [BXP2N65D](#) [BXT1150N10J](#) [BXT1700P06M](#) [TSM60NB380CP ROG](#) [RQ7L055BGTCR](#) [DMNH15H110SK3-13](#)
[SLF10N65ABV2](#) [BSO203SP](#) [BSO211P](#) [IPA60R230P6](#)