



SCHOTTKY BARRIER RECTIFIERS


Reverse Voltage - 40 to 200 V

Forward Current - 20 A




FEATURES

- High current capability
- Low forward voltage drop
- Low power loss, high efficiency
- High surge capability
- High temperature soldering guaranteed
- Mounting position: any

TO-251(I-PAK)



TO-252(D-PAK)



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified

| CHARACTERISTICS | TO-251 | MBR2040VT | MBR2045VT | MBR2060VT | MBR20100VT | MBR20150VT | MBR20200VT | Units | |
|---|-----------------|------------|-----------|-----------|------------|------------|------------|-------|----|
| | TO-252 | MBR2040DT | MBR2045DT | MBR2060DT | MBR20100DT | MBR20150DT | MBR20200DT | | |
| Maximum Recurrent Peak Reverse Voltage | V_{RRM} | 40 | 45 | 60 | 100 | 150 | 200 | V | |
| Maximum RMS voltage | V_{RMS} | 28 | 31.5 | 42 | 70 | 105 | 140 | V | |
| Maximum DC Blocking Voltage | V_{DC} | 40 | 45 | 60 | 100 | 150 | 200 | V | |
| Maximum Average Forward Rectified Current | $I_{F(AV)}$ | 20 | | | | | | A | |
| Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method) | I_{FSM} | 150 | | | | | | A | |
| Max Instantaneous Forward Voltage at 10 A DC per leg | V_F | 0.70 | | 0.75 | 0.85 | 0.90 | 0.92 | V | |
| Maximum DC Reverse Current $T_a = 25^\circ\text{C}$ at Rated DC Reverse Voltage $T_a = 125^\circ\text{C}$ | I_R | 0.1 20 | | | 0.05 20 | | | mA | |
| Typical Junction Capacitance ⁽¹⁾ | C_j | 600 | | 400 | | | | pF | |
| Typical Thermal Resistance ⁽²⁾ | $R_{\theta JA}$ | 45 | | | | | | °C/W | |
| Operating Junction Temperature Range | T_j | -55 ~ +150 | | | | -55 ~ +175 | | | °C |
| Storage Temperature Range | T_{stg} | -55 ~ +150 | | | | -55 ~ +175 | | | °C |

(1) Measured at 1 MHz and applied reverse voltage of 4 V D.C

(2) P.C.B. mounted with 10cmX10cmX1mm copper pad areas.



Fig.1 TYPICAL FORWARD CURRENT DERATING CURVE




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Forward Characteristic




Fig.4 Typical Junction Capacitance




Fig.5 Maximum Non-Repetitive Peak Forward Surge Current






Fig.6- Typical Transient Thermal Impedance





TO-251(D-PAK) Package Outline Dimensions



TO-251(I-PAK) mechanical data

| UNIT | | A | B | b | b1 | C | D | E | F | G | H | L | L1 | M | N |
|------|-----|-----|-----|-----|------|-----|-----|-----|-----|-----------------|------|-----|-----|----------------|----------------|
| mm | max | 6.7 | 5.5 | 0.8 | 0.9 | 2.5 | 6.3 | 0.6 | 1.8 | 2.29 TYPICAL | 0.55 | 4.3 | 1.2 | 1.8 TYPICAL | 1.3 TYPICAL |
| | min | 6.3 | 5.1 | 0.3 | 0.76 | 2.1 | 5.9 | 0.4 | 1.3 | | 0.45 | 3.9 | 0.8 | | |
| mil | max | 264 | 217 | 31 | 35 | 98 | 248 | 24 | 71 | 90 TYPICAL | 22 | 169 | 47 | 71 TYPICAL | 51 TYPICAL |
| | min | 248 | 201 | 12 | 30 | 83 | 232 | 16 | 51 | | 18 | 154 | 31 | | |

Important Notice and Disclaimer

Jingdao Microelectronics reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

Jingdao Microelectronics makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, not does Jingdao Microelectronics assume any liability for application assistance or customer product design. Jingdao Microelectronics does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of Jingdao Microelectronics.

Jingdao Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of Jingdao Microelectronics.



TO-252(D-PAK) Package Outline Dimensions



TO-252(D-PAK) mechanical data

| UNIT | | A | B | b | C | D | E | F | G | H | L | L1 | L2 | L3 | S | M | N | J | K | T |
|------|-----|-----|-----|-----|-----|-----|-----|-----|-----------------|------|-----|-----|-----|------|-----|----------------|----------------|------|------|------|
| mm | max | 6.7 | 5.5 | 0.8 | 2.5 | 6.3 | 0.6 | 1.8 | 2.29 TYPICAL | 0.55 | 3.1 | 1.2 | 1.0 | 1.75 | 0.1 | 1.8 TYPICAL | 1.3 TYPICAL | 3.16 | 1.80 | 4.83 |
| | min | 6.3 | 5.1 | 0.3 | 2.1 | 5.9 | 0.4 | 1.3 | | 0.45 | 2.7 | 0.8 | 0.6 | 1.40 | 0.0 | | | ref. | ref. | ref. |
| mil | max | 264 | 217 | 31 | 98 | 248 | 24 | 71 | 90 TYPICAL | 22 | 122 | 47 | 39 | 69 | 4 | 71 TYPICAL | 51 TYPICAL | 124 | 71 | 190 |
| | min | 248 | 201 | 12 | 83 | 232 | 16 | 51 | | 18 | 106 | 31 | 24 | 55 | 0 | | | ref. | ref. | ref. |

Jingdao Microelectronics reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

Jingdao Microelectronics makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Jingdao Microelectronics assume any liability for application assistance or customer product design. Jingdao Microelectronics does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of Jingdao Microelectronics.

Jingdao Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of Jingdao Microelectronics.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Schottky Diodes & Rectifiers](#) category:

Click to view products by [Jingdao](#) manufacturer:

Other Similar products are found below :

[CUS06\(Te85L,Q,M\)](#) [MA4E2039](#) [D1FH3-5063](#) [MBR0530L-TP](#) [MBR10100CT-BP](#) [MBR30H100MFST1G](#) [MMBD301M3T5G](#) [PMAD1103-LF](#) [PMAD1108-LF](#) [RB160M-50TR](#) [RB520S-30](#) [RB551V-30](#) [DD350N18K](#) [DZ435N40K](#) [DZ600N16K](#) [BAS16E6433HTMA1](#) [BAS 3010S-02LRH E6327](#) [BAT 54-02LRH E6327](#) [IDL02G65C5XUMA1](#) [NSR05F40QNXT5G](#) [NSVR05F40NXT5G](#) [JANS1N6640](#) [SB07-03C-TB-H](#) [SB1003M3-TL-W](#) [SBAT54CWT1G](#) [SBM30-03-TR-E](#) [SBS818-TL-E](#) [SK32A-LTP](#) [SK33A-TP](#) [SK34A-TP](#) [SK34B-TP](#) [SMD1200PL-TP](#) [ACDBN160-HF](#) [SS3003CH-TL-E](#) [STPS30S45CW](#) [PDS3100Q-7](#) [GA01SHT18](#) [CRS10I30A\(Te85L,QM\)](#) [MBR1240MFST1G](#) [MBRB30H30CT-1G](#) [BAS28E6433HTMA1](#) [BAS 70-02L E6327](#) [HSB123JTR-E](#) [JANTX1N5712-1](#) [VS-STPS40L45CW-N3](#) [DD350N12K](#) [SB007-03C-TB-E](#) [SB10015M-TL-E](#) [SB1003M3-TL-E](#) [SK110-LTP](#)