

Performance Specification

| Model | I _{hold} | I _{trip} | V _{max} | V _{max} | I _{max} | P _d | Maximum Time | | Resistance | | |
|-------------|-------------------|-------------------|------------------|------------------|------------------|----------------|----------------|---------------|---------------------|---------------------|---------------------|
| | | | Operating | Interrupt | | | To Trip | | R _{i min.} | R _{i max.} | R _{1 max.} |
| | (mA) | (mA) | (Vdc) | (Vrms) | (A) | Typ. | Current (A) | Time (Sec) | (Ω) | (Ω) | (Ω) |
| JK250-020U | 20 | 45 | 60 | 250 | 3 | 1.00 | 0.5 | 0.4 | 80 | 160 | 240 |
| JK250-030U | 30 | 65 | 60 | 250 | 3 | 1.00 | 0.5 | 0.5 | 60 | 120 | 180 |
| JK250-040U | 40 | 80 | 60 | 250 | 3 | 1.00 | 0.5 | 1.0 | 30 | 60 | 100 |
| JK250-060U | 60 | 120 | 60 | 250 | 3 | 1.00 | 0.5 | 0.5 | 20 | 60 | 90 |
| JK250-080U | 80 | 160 | 60 | 250 | 3 | 1.00 | 1.00 | 0.4 | 14 | 22 | 33 |
| JK250-090U | 90 | 180 | 60 | 250 | 3 | 1.00 | 1.00 | 0.5 | 10 | 20 | 31 |
| JK250-110U | 110 | 200 | 60 | 250 | 3 | 1.00 | 1.00 | 1.2 | 6.0 | 12 | 16 |
| JK250-120 | 120 | 240 | 60 | 250 | 3 | 1.00 | 1.00 | 1.2 | 5.0 | 10 | 14 |
| JK250-120U | 120 | 240 | 60 | 250 | 3 | 1.00 | 1.00 | 1.2 | 6.0 | 11 | 16 |
| JK250-145U | 145 | 290 | 60 | 250 | 3 | 1.00 | 1.00 | 4 | 3.5 | 6.5 | 14 |
| JK250-180T | 180 | 650 | 60 | 250 | 10 | 1.00 | 1.00 | 1.5 | 1.0 | 2.2 | 4.0 |
| JK250-180U | 180 | 650 | 60 | 250 | 10 | 1.00 | 3.00 | 1.5 | 1.0 | 3.0 | 5.0 |
| JK250-200U | 200 | 400 | 60 | 250 | 10 | 1.00 | 3.00 | 5.0 | 3.0 | 6.0 | 9.0 |
| JK250-400U | 400 | 800 | 60 | 250 | 10 | 1.00 | 3.00 | 8.0 | 1.0 | 3.0 | 6.0 |
| JK250-600U | 600 | 1200 | 60 | 250 | 10 | 1.00 | 3.00 | 12.0 | 0.6 | 2.0 | 5.0 |
| JK250-800U | 800 | 1600 | 60 | 250 | 10 | 1.50 | 5.00 | 18.0 | 0.4 | 1.0 | 3.0 |
| JK250-1000U | 1000 | 2000 | 60 | 250 | 10 | 1.50 | 5.00 | 20.0 | 0.3 | 0.8 | 2.0 |
| JK250-1200U | 1200 | 2400 | 60 | 250 | 10 | 1.50 | 6.00 | 20.0 | 0.2 | 0.8 | 2.0 |
| JK250-1500U | 1500 | 3000 | 60 | 250 | 10 | 1.50 | 7.50 | 20.0 | 0.2 | 0.6 | 1.5 |
| JK250-2000U | 2000 | 4000 | 60 | 250 | 10 | 1.50 | 10.00 | 20.0 | 0.2 | 0.4 | 1.5 |

V_{max} = Maximum operating voltage device can withstand without damage at rated current (I_{max}).

I_{max} = Maximum fault current device can withstand without damage at rated voltage (V_{max}).

I_{hold} = Hold Current. Maximum current device will not trip in 25°C still air.

I_{trip} = Trip Current. Minimum current at which the device will always trip in 25°C still air.


P_d = Power dissipation when device is in the tripped state in 25°C still air environment at rated voltage.

R_{i min./max} = Minimum/Maximum device resistance prior to tripping at 25°C.

R_{1max} = Maximum device resistance is measured one hour post reflow.

CAUTION : Operation beyond the specified ratings may result in damage and possible arcing and flame.

Physical Dimensions(mm.)



| Model | A | B | C | D | E |
|------------|------|------|------|------|------|
| | Max. | Max. | Typ. | Min. | Max. |
| JK250-080 | 6.5 | 12.0 | 5.1 | 5.0 | 3.8 |
| JK 250-090 | 6.5 | 12.0 | 5.1 | 5.0 | 3.8 |
| JK 250-110 | 6.5 | 15.0 | 5.1 | 5.0 | 3.8 |
| JK 250-120 | 7.0 | 15.0 | 5.1 | 5.0 | 3.8 |
| JK 250-145 | 7.0 | 13.5 | 5.1 | 5.0 | 3.8 |
| JK 250-180 | 10.5 | 16.5 | 5.1 | 5.0 | 3.8 |



Environmental Specifications

| Test | Conditions | Resistance change |
|-----------------------|-----------------------------|-------------------|
| Passive aging | +85°C, 1000 hrs. | ±5% typical |
| Humidity aging | +85°C, 85% R.H. , 168 hours | ±5% typical |
| Thermal shock | +85°C to -40°C, 20 times | ±33% typical |
| Resistance to solvent | MIL-STD-202, Method 215 | No change |
| Vibration | MIL-STD-202, Method 201 | No change |

Ambient operating conditions : - 40 °C to +85 °C



Maximum surface temperature of the device in the tripped state is 125 °C

Agency Approval and Environmental Compliance

| Agency | File Number | Regulation | Standard |
|--------|-------------|--|------------|
| UL | pending |  | 2002/95/EC |
| TUV | pending |  | R50077227 |

Thermal Derating Curve


Average Time-Current Curve



Ihold Versus Temperature

| Model | Maximum ambient operating temperature (T_{mao}) vs. hold current (I_{hold}) | | | | | | | | |
|------------|---|-------|-------|-------|-------|-------|-------|-------|-------|
| | -40°C | -20°C | 0°C | 25°C | 40°C | 50°C | 60°C | 70°C | 85°C |
| JK250-080 | 0.124 | 0.110 | 0.095 | 0.080 | 0.066 | 0.059 | 0.051 | 0.044 | 0.033 |
| JK 250-090 | 0.140 | 0.124 | 0.107 | 0.090 | 0.074 | 0.066 | 0.057 | 0.050 | 0.037 |
| JK 250-110 | 0.171 | 0.151 | 0.131 | 0.110 | 0.091 | 0.081 | 0.071 | 0.061 | 0.046 |
| JK 250-120 | 0.186 | 0.165 | 0.143 | 0.120 | 0.099 | 0.088 | 0.077 | 0.066 | 0.050 |
| JK 250-145 | 0.225 | 0.199 | 0.172 | 0.145 | 0.119 | 0.106 | 0.093 | 0.080 | 0.060 |
| JK 250-180 | 0.279 | 0.247 | 0.213 | 0.180 | 0.147 | 0.131 | 0.115 | 0.099 | 0.074 |

Soldering Parameters




WAVE SOLDERING INFORMATIONS

| | |
|------------------|---|
| Pre-Heating Zone | Max. ramping rate should not exceed 4°C/Sec. |
| Soldering Zone | Max. solder temperature should not exceed 260°C |
| Cooling Zone | Cooling by natural convection in air. |

© Specifications are subject to change without notice.

Packaging Quantity



| E | P | P0 | P1 | W1 | w | H | D |
|-----------|----------|----------|------------|----------|--------|------------|-----------|
| 5.0±0.5mm | 12.7±1mm | 12.7±1mm | 3.85±0.7mm | 12 (min) | 18±1mm | 16.5±1.0mm | 4.0±0.5mm |

Package Qty: 1000PCS/small box, 10 boxes/Carton

Small Box Dim: 330 (±4) mm×245 (±3) mm×43 (±2) mm

Carton Dim: 500 (±5) mm×350 (±4) mm×265 (±3) mm

| JK250 | 120 | U | Reel Q'ty | Bag Q'ty |
|---------|---------|-----------------|-----------|----------|
| Product | Hold | T= Pre-tripped | 1000PCS | 1000PCS |
| name | Current | U= Uncoated | | |
| 250V | (mA) | Blank= Standard | | |

Tape & Reel packaging per EIA468-B standard.

Warehouse Storage Conditions of Product s

(1) Storage Conditions :

- a.Storage Temperature : -10℃~+40℃
- b.Relative Humidity : ≅75%RH
- c. Keep away from corrosive atmosphere and sunlight.

(2) Period of Storage : 1 year

Website: <http://www.jksemit.com>

For additional information, please contact your local Sales Representative.

©Copyright 2016, jksemit



is a registered trademark of jksemit All rights are reserved

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Resettable Fuses - PPTC](#) category:

Click to view products by [Jinkaisheng](#) manufacturer:

Other Similar products are found below :

[RF0077-000](#) [RF0627-000](#) [RF3301-000](#) [RF3382-000](#) [RF3394-000](#) [RF3399-000](#) [SMD125-2](#) [RF1973-000](#) [RF2531-000](#) [RF2873-000](#) [RF3060-000](#) [RF3311-000](#) [TR600-150Q-B-0.5-0.130](#) [RXE090](#) [5E4795/04-1502](#) [TRF250-080T-B-1.0-0.125](#) [SMD100-2](#) [NIS5431MT1TXG](#) [SMD250-2](#) [RS30-090](#) [RS30-600](#) [RS30-800](#) [RS30-900](#) [RS60RB-160](#) [RS60SB-250](#) [SB250-145](#) [K30U400](#) [0ZCH0110AF2E](#) [BK60-110-DI-E0.6](#) [BK250-120-SZ-E0.6](#) [BK60-010-DI-E0.5](#) [BK250-040-DY-E0.6](#) [RF2631-000](#) [NIS4461MT3TXG](#) [NIS5420MT2TXG](#) [NIS5420MT3TXG](#) [NIS6420MT1TWG](#) [RF5032-000](#) [RF5051-000](#) [RF5105-000](#) [RF5062-000](#) [RF5055-000](#) [RF5052-000](#) [2920L075/72MR](#) [BSMD0603-025-24V](#) [BSMD0402L-005](#) [BSMD0603-010-9V](#) [BSMD1812-020-60V](#) [BSMD2920-400-30V](#) [BSMD0603-010-12V](#)