

OUTSIDE D	DIAMETER	TUDEADO	DEDTIL	RADIUS OF THREAD	
MAJOR CREST OF THREAD	MINOR ROOT OF THREAD	THREADS PER INCH	DEPTH OF THREAD		
MIN206" (5.23mm)		25.4	.011" MIN.	.0116" (.29mm)	
MAX210" (5.33mm)	MAX188" (4.77mm)		(.28mm)		

JKL LAMP	VOLTS	AMPS	MSCP	LUMENS	AVERAGE	FILAMENT
NUMBER	RATED	±10%	±25%	±25%	LIFE HRS.	TYPE
1769	2.5	.200	.200	2.51	500	C-2R
373	14.0	.080	.500	6.29	2,500	C-2F
8384	28.0	.040	.200	2.51	50,000	C-2F
335	28.0	.040	.340	4.27	4,000	C-2F
8369	28,0	.065	.650	8.17	5,000	C-2F

			METRIC	DIMENSI IN MILLI	ONS ARE METERS		IKI	[]	OMPON	TENT	S COD	DOD AT	ION
				TOLERANG	CE UNLESS	-			OMIFOR	4 TO 1.4 I	S COR	TUKAI	1011
				OTHERWISE 1 PL +/		TITLE							
			THIRD ANGLE	2 PL +/		Ι т.	-1 3/4 S	TAND	ARD MIT	GET	SCREW	RASEI	AMP
			PROJECTION	ANGLE +/- 0		T-1 3/4 STANDARD MIDGET SCREW BASE LAMP							
			DRAWN BY	APPV'D BY	DATE	SIZE		DRAWIN					
Α	DELETE NOTE	4/9/01	L. WENGSTROM	E.D.	4/9/01	Α	55335	NO.	SCREW	/ BAS	SE T-1	3/417.	4
	RELEASE & CANCEL 335LSV	11/17/00	- CAD D	DAWING	· _	SCALE		RELEAS	ED	REVISIO	N	REV.	SHEET
REV		APPV'D	- OAD BIVAVIIVO -					DATE 11/17/00				NO. A	la al
NO.	NUMBER	DATE	MANUAL REVISIO	NS NOT PER	RMITTED		INOINE		11/1//00		10101		TOFT

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Lamps category:

Click to view products by JKL manufacturer:

Other Similar products are found below:

5AB 6180 8111 8623 912 120PS 1224 DE603 DW50 IFL-LX2162-16T C9A C9A 3015 303 19 PR13 268 GT-NE6H1225T

CM5004WW 32-2211T 509K 5314N1 5314N2 WWT1-EW10/GRN 4925H1 DW07 1141 MS25231-313 E73 CM2 7683EBP 8553

XE135B WWT2-EW34BLA 6S6/30V 7367 1301910036 7A1H 8630FBBB WT3F-20 85 106 105 BGF717-UV1 1974D 1495 373 400

502 67