

JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	MSCP ±25%	LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE
11	2.5	.200	.200	2.51 1.89	500	C-2R C-2R
56 79	5.0 6.0	.115 .200	.150 .630	7.92	40,000 1,000	C-2R C-2R
86	6.3	.200	.400	5.03	50,000	C-2F
18*	14.0	.040	.130	1.63	5,000	C-2F
73*	14.0	.080	.300	3.77	15,000	C-2F
37	14.0	.090	.500	6.29	2,500	C-2F
74	14.0	.100	.700	8.80	500	C-2F
85	28.0	.040	.300	3.77	25,000	C-2F
17	28.0	.065	.650	8.17	5,000	C-2F

*LAMP LEAD (Pb) FREE

CONTACT JKL FOR LEAD (Pb) FREE LOT IDENTIFICATION.

			METRIC	IN MILL	IONS ARE IMETERS		IKI		MPON	JENT	S CORI	PORAT	ION
	1	<u> </u>	THIRD ANGLE			TITLE					S WEDG		
			PROJECTION	ANGLE +									-
В	CHANGE #18 TO LEAD (Pb) FREE	7/12/05	DRAWN BY	APPV'D BY	DATE	SIZE	FSCM NO.						
Α	NOTE #73 TO LEAD (Pb) FREE	2/17/05	L. WENGSTROM	J.K.	7/12/05	Α	55335	NO.	GLAS:	S WE	DGE B	ASE T-	1 3/4
	RELEASED & CANCEL GW-STD-T1 3/4, 75X & 84	5/11/00			SCALE		RELEASED		REVISION		REV.	SHEET	
RE\ NO.		APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SOALE	NONE		/11/00	DATE	7/12/05	NO. B	1 _{OF} 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Lamps category:

Click to view products by JKL manufacturer:

Other Similar products are found below:

5AB 6180 8111 8623 912 120PS 1224 DE603 DW50 IFL-LX2162-16T C9A C9A 3015 303 19 PR13 268 GT-NE6H1225T

CM5004WW 32-2211T 509K 5314N1 5314N2 WWT1-EW10/GRN 4925H1 DW07 1141 MS25231-313 E73 CM2 7683EBP 8553

XE135B WWT2-EW34BLA 6S6/30V 7367 1301910036 7A1H 8630FBBB WT3F-20 85 106 105 BGF717-UV1 1974D 1495 400 502

67 PR12