



JKL LAMP PART NO.	COLOR WHITE 6900°KELVIN	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) MINIMUM
BF20125-28B	x = .325 y = .295	700 @ 0°C	280	5	38,000 TYP.	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

<p>METRIC THIRD ANGLE PROJECTION</p>	<p>DIMENSIONS ARE IN MILLIMETERS</p> <p>TOLERANCE UNLESS OTHERWISE SPECIFIED</p> <p>1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0</p>	<p>JKL COMPONENTS CORPORATION</p>					
		<p>TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP</p>					
<p>DRAWN BY L. WENGSTROM</p>	<p>APPVD BY L.R.</p>	<p>DATE 7/30/09</p>	<p>SIZE A</p>	<p>FSCM NO. 55335</p>	<p>DRAWING NO. BF20125-28B</p>		
<p>- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED</p>			<p>SCALE NONE</p>	<p>RELEASED DATE 4/22/04</p>	<p>REVISION DATE 7/30/09</p>	<p>REV. NO. A</p>	<p>SHEET 1 OF 1</p>

REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE
A	RATED LIFE HRS MINIMUM RELEASE & CANCEL P-0404-14	7/30/09 4/22/04

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [CCFL Fluorescent Lamps](#) category:

Click to view products by [JKL](#) manufacturer:

Other Similar products are found below :

[BF20170-38B](#) [BF4142-20B](#) [BF20137-26B](#) [BF2698-20B](#) [CF20228-31B](#) [CF26349-28B](#) [BF22140-24B](#) [BF22180-28B](#) [BF26180-24B](#) [BF5118-20B](#) [BF20125-28B](#) [BF20325-24B](#) [BF26214-20B](#) [BF26230-24B](#) [BF26240-24B](#) [BF26250-24B](#) [BF2661-24B](#) [BF386-20B](#) [BF20218-24B](#) [BF20226-24B](#) [BF20292-24B](#) [BF22258-25B](#) [BF22312-45B](#) [BF26318-20B](#) [BF3100-20B](#) [BF3228-21B](#) [BF5165-20B](#) [CF20305-24B](#) [BF3300-20B](#) [BF350-20B](#)