



JKL LAMP PART NO.	COLOR WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) MINIMUM
BF20170-38B	x = 0.356±0.02 y = 0.326±0.02	1000 @ 0°C	400	5	35,000 TYP.	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

NOTE 1: MERCURY (Hg) CONTENT: 2.4mg/LAMP MAX.

 THIRD ANGLE PROJECTION	DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0	JKL COMPONENTS CORPORATION			
		TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP			
DRAWN BY L. WENGSTROM	APPVD BY L.R.	DATE 7/30/09	SIZE A	FSCM NO. 55335	DRAWING NO. BF20170-38B
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE NONE	RELEASED DATE 12/15/04	REVISION DATE 7/30/09
REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE	REV. NO.	SHEET	1 OF 1

A	RATED LIFE HRS MINIMUM	7/30/09
	RELEASE & CANCEL P-0410-02	12/15/04
REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [CCFL Fluorescent Lamps](#) category:

Click to view products by [JKL](#) manufacturer:

Other Similar products are found below :

[BF20170-38B](#) [BF4142-20B](#) [BF20137-26B](#) [BF2698-20B](#) [CF20228-31B](#) [CF26349-28B](#) [BF22140-24B](#) [BF22180-28B](#) [BF26180-24B](#) [BF5118-20B](#) [BF20125-28B](#) [BF20325-24B](#) [BF26214-20B](#) [BF26230-24B](#) [BF26240-24B](#) [BF26250-24B](#) [BF2661-24B](#) [BF386-20B](#) [BF20218-24B](#) [BF20226-24B](#) [BF20292-24B](#) [BF22258-25B](#) [BF22312-45B](#) [BF26318-20B](#) [BF3100-20B](#) [BF3228-21B](#) [BF5165-20B](#) [CF20305-24B](#) [BF3300-20B](#) [BF350-20B](#)