



JKL PART NUMBER	COLOR RGB WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) MINIMUM
BF22180-28B	x = .346 y = .319	1140 @ 0°C	380	5 ± 1	38,000 ±10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION				
			TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP						
B RATED LIFE HRS MINIMUM 7/30/09 A CIRCUIT & LAMP VOLTAGE CHANGE 7/19/04 RELEASED & CANCEL P-0303-14 9/2/03			DRAWN BY L. WENGSTROM APPVD BY L.R. DATE 7/30/09		SIZE A	FSCM NO. 55335	DRAWING NO. BF22180-28B		
REV. NO. DESCRIPTION/ECO NUMBER APPVD DATE			- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE	RELEASED DATE 9/2/03	REVISION DATE 7/30/09	REV. NO. B	SHEET 1 OF 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [CCFL Fluorescent Lamps](#) category:

Click to view products by [JKL](#) manufacturer:

Other Similar products are found below :

[BF20170-38B](#) [BF4142-20B](#) [BF20137-26B](#) [BF2698-20B](#) [CF20228-31B](#) [CF26349-28B](#) [BF22140-24B](#) [BF22180-28B](#) [BF26180-24B](#) [BF5118-20B](#) [BF20125-28B](#) [BF20325-24B](#) [BF26214-20B](#) [BF26230-24B](#) [BF26240-24B](#) [BF26250-24B](#) [BF2661-24B](#) [BF386-20B](#) [BF20218-24B](#) [BF20226-24B](#) [BF20292-24B](#) [BF22258-25B](#) [BF22312-45B](#) [BF26318-20B](#) [BF3100-20B](#) [BF3228-21B](#) [BF5165-20B](#) [CF20305-24B](#) [BF3300-20B](#) [BF350-20B](#)