



JKL PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS) TYPICAL
BF22258-25B	LCD HIGH OUTPUT WHITE 9700°k RGB	1600 @ 0°C	535	5 ± 1	38,000 ±10%	50,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

METRIC THIRD ANGLE PROJECTION			DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0			JKL COMPONENTS CORPORATION					
F RATED LIFE HRS. TYPICAL & 20,000 TO 50,000 8/19/09 E ADD MINIMUM TO RATED LIFE HRS. 7/16/09 D CHANGE ON ELECT. CHART 4/16/09 C CHANGE ON CIRCUIT & LAMP VOLTAGE 7/19/04 B CHANGE ON OUTPUT RGB 11/11/02 A NEW CHART 6/5/01 RELEASED 6/4/01			DRAWN BY L. WENGSTROM APPV'D BY L.R. DATE 8/19/09			SIZE A SCALE NONE		FSCM NO. 55335 DRAWING NO. BF22258-25B		TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP	
REV. NO. DESCRIPTION/ECO NUMBER APPV'D DATE			- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			RELEASED DATE 6/4/01		REVISION DATE 8/19/09		REV. NO. F SHEET 1 OF 1	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [CCFL Fluorescent Lamps](#) category:

Click to view products by [JKL](#) manufacturer:

Other Similar products are found below :

[BF20170-38B](#) [BF4142-20B](#) [BF20137-26B](#) [BF2698-20B](#) [CF20228-31B](#) [CF26349-28B](#) [BF22140-24B](#) [BF22180-28B](#) [BF26180-24B](#) [BF5118-20B](#) [BF2698-31BASSY](#) [BF20125-28B](#) [BF20325-24B](#) [BF26214-20B](#) [BF26230-24B](#) [BF26240-24B](#) [BF26250-24B](#) [BF2661-24B](#) [BF386-20B](#) [BF20218-24B](#) [BF20226-24B](#) [BF20292-24B](#) [BF22258-25B](#) [BF22312-45B](#) [BF26318-20B](#) [BF3100-20B](#) [BF3228-21B](#) [BF5165-20B](#) [CF20305-24B](#) [BF3300-20B](#) [BF350-20B](#)