


JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF26318-20B	LCD HIGH OUTPUT WHITE 5300°k RGB	1636 @ 0°C	676	5	34,000 ± 10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION					
			DRAWN BY L. WENGSTROM		APP'VD BY DATE F.D. 2/28/02		SIZE A		FSCM NO. 55335		DRAWING NO. BF26318-20B	
RELEASED 2/28/02			APP'VD DATE		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE		RELEASED DATE 2/28/02		REVISION DATE	
REV. NO.	DESCRIPTION/ECO NUMBER		APP'VD DATE					SCALE	RELEASED DATE	REVISION DATE	REV. NO.	SHEET 1 OF 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [CCFL Fluorescent Lamps](#) category:

Click to view products by [JKL](#) manufacturer:

Other Similar products are found below :

[BF20170-38B](#) [BF4142-20B](#) [BF20137-26B](#) [BF2698-20B](#) [CF20228-31B](#) [CF26349-28B](#) [BF22140-24B](#) [BF22180-28B](#) [BF26180-24B](#) [BF5118-20B](#) [BF2698-31BASSY](#) [BF20125-28B](#) [BF20325-24B](#) [BF26214-20B](#) [BF26230-24B](#) [BF26240-24B](#) [BF26250-24B](#) [BF2661-24B](#) [BF386-20B](#) [BF20218-24B](#) [BF20226-24B](#) [BF20292-24B](#) [BF22258-25B](#) [BF22312-45B](#) [BF26318-20B](#) [BF3100-20B](#) [BF3228-21B](#) [BF5165-20B](#) [CF20305-24B](#) [BF3300-20B](#) [BF350-20B](#)