

JKL PART NUMBER	- A - LENGTH	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C TYP.	OPERATING LAMP VOLTAGE VL (Vrms) TYP.	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2) TYPICAL	*RATED LIFE (HRS) AVERAGE	
BF350-20B	50 +/- 2.0		425	170	5 ± 1	31,000	40,000	
BF375-20B	75 +/- 2.0	RGB	515	205	5 ± 1	31,000	40,000	
BF386-20B	86 +/- 2.0	HIGH OUTPUT WHITE 5400° KELVIN (REF.)	540	215	5 ± 1	31,000	40,000	
BF3100-20B	100 +/- 2.0		640	255	5 ± 1	31,000	40,000	
BF3115-20B	115 +/- 2.0		725	290	5 ± 1	31,000 31,000 31,000 31,000	40,000	
BF3130-20B	130 +/- 2.0		775	310	5 ± 1			
BF3160-20B	160 +/- 2.0		900	360	5 ± 1		40,000	
BF3180-20B	180 +/- 2.0		950	380	5 ± 1			
BF3216-20B	216 +/- 2.0	x = .340	1125	450	5 ± 1	31,000	40,000	
BF3240-20B	240 +/- 2.0	y = .360	1240	495	5 ± 1	31,000	40,000	
BF3250-20B	250 +/- 2.0		1300	520	5 ± 1	31,000	40,000	
BF3275-20B	275 +/- 2.0		1475	590	5 ± 1	31,000	40,000	
BF3300-20B	300 +/- 1.5		1625	650	5 ± 1	31,000	40,000	
BF3360-20B	360 +/- 2.0		1850	740	5 ± 1	31,000	40,000	
BF3380-20B	380 +/- 2.0		1975	790	5 ± 1	31,000	40,000	

\*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

J	CHNG LEAD LTH & BRIGHTNESS TO 31,000 TYP	12/30/09									
	CHANGE LEAD LENGTH TOLERANCE		METRIC	DIMENSIONS A		1	rt/i	ľ			
Н	CHANGE BF3300-20B LENGTH TOLERANCE		1	IN MILLIMETER	s			• COMPO	NENTS COR	DOD A T	TON
G	B ELECTRICAL MODIFICATIONS			TOLERANCE UNLE	SS	•		COMPO	VEN 12 COK	PUKAI	ION
F	ADD PART NUMBER BF3115-20B		<del> (•)(- </del> +	OTHERWISE SPECIF	ED T	TITLE		LATURE COL			
E	ADD PART NUMBER BF3180-20B & BF3380-20B	11/30/01	1 4 -	1 PL +/- 0.2			MIN	IATURE COLI	J CATHODE		
D	ADD PART NUMBER BF3240-20B	4/26/01	THIRD ANGLE	2 PL +/- 0.20			FIII	ORESCENT L	ΔMP		
С	ADD PART NUMBER BF3130-20B	9/11/00	PROJECTION	ANGLE +/- 0							
В	ADD PART NUMBER BF375-20B	4/21/00	DRAWN BY	APPV'D BY DAT	∃ S	SIZE	1	DRAWING			
Α	LENGTH ±5 TO ±2	2/25/00	L. WENGSTROM	L.R. 12/30	09	Α	55335	I <sup>NO.</sup> BF	· 3-20B		
	RELEASED - CANCEL BF-3mm DIA DRAWING	2/21/00	0455	DAMAINO.	SI	CALE		RELEASED	REVISION	REV.	SHEET
REV	. DESCRIPTION/ECO	APPV'D						DATE 2/21/00	DATE 12/30/09	NO	1 1
NO.	O. NUMBER		MANUAL REVISIONS NOT PERMITTED				NONE	2/2 1/00	12/30/09	NO. J	I OF I

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for CCFL Fluorescent Lamps category:

Click to view products by JKL manufacturer:

Other Similar products are found below:

BF20170-38B BF4142-20B BF6200-20B BF20137-26B BF2698-20B BF6150-20B BF3380-20B CF26349-28B BF3130-20B BF3137
32B/ASSY/01 BF22140-24B BF22180-28B BF23312-24B BF24438-33B BF26180-24B BF26360-20B BF5118-20B CF20305-24B

BF2698-31BASSY BF20125-28B BF20325-24B BF22160-24B BF26214-20B BF26230-24B BF26240-24B BF26250-24B BF2661-24B

BF3216-20B BF386-20B BF3300-20B BF350-20B BF20218-24B BF20226-24B BF20292-24B BF22258-25B BF22312-45B BF26188-20B

BF26318-20B BF3100-20B BF3228-21B BF5165-20B