

JKL LAMP PART NUMBER	COLOR LCD HIGH OUTPUT WHITE 6720°k RGB	STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS) AVERAGE
BF3228-21B	x = .315 y = .295	1190	475	5 ± 1	28,000 ± 10%	40,000

^{*} RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

		METRIC	DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION								
		THIRD ANGLE PROJECTION			MINIATURE COLD CATHODE FLUORESCENT LAMP								
В	ELECTRICAL RATING CHANGES	8/5/04	DRAWN BY	APPV'D BY	DATE	SIZE	FSCM NO.	DRAWING					
Ā		0,20,0.	L. WENGSTROM	J.K.	8/5/04	Α	55335	NO.	BF3	3228-	21B		
		12/95	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE	•	RELEASED		REVISION		REV.	SHEET
REV NO.		APPV'D DATE				NONE	DATE 12/9	95	DATE	8/5/04	NO. B	1 _{OF} 1	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for CCFL Fluorescent Lamps category:

Click to view products by JKL manufacturer:

Other Similar products are found below:

BF20170-38B BF4142-20B BF20137-26B BF2698-20B CF20228-31B CF26349-28B BF22140-24B BF22180-28B BF26180-24B BF5118-20B BF20125-28B BF20325-24B BF26214-20B BF26230-24B BF26240-24B BF26250-24B BF2661-24B BF386-20B BF20218-24B BF20226-24B BF20292-24B BF22258-25B BF22312-45B BF26318-20B BF3100-20B BF3228-21B BF5165-20B CF20305-24B BF3300-20B BF350-20B