

JKL PART NUMBER	LENGTH A +/- 2mm	COLOR (REF.)	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF5118-20B	118mm	RGB	600	305	5 ± 1	7000 ± 700	20,000
BF5165-20B	165mm	HIGH	800	400	5 ± 1	7000 ± 700	20,000
BF5200-20B	200mm	WHITE 5400° KELVIN	850	445	5 ± 1	7000 ± 700	20,000
BF5300-20B	300mm		1000	600	5 ± 1	7000 ± 700	20,000

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

		METRIC		ISIONS LIMETI			K		OMPO	TIT NIT	'S CODI	DOD A	FION	
	1	1	\oplus	OTHERV	ANCE UNI VISE SPEC _ +/- 0.	CIFIED	TITLE	SIN		LEAD TIF				HON
			THIRD ANGLE PROJECTION	2 PL +/- 0 ANGLE +/- 0			FLUORESCENT LAMP							
			DRAWN BY	APPV'D	BY D	ATE	SIZE	FSCM NO.				_		
Α	6.3 TO 6.2 MAX., ADD 5.0 DIM.	2/29/00	L. WENGSTROM	JK	02/29	/00	Α	55335	NO.	BF	5-20	В		
	RELEASED - CANCEL BF-5mm DIA DRAWING	2/25/00	CADD	DAWING SCA		SCALE		RELEAS	FD	REVISIO	N	REV.	SHEET	
REV.			- CAD DRAWING -					2/25/00	DATE			4 4		
NO.	NUMBER	DATE	E MANUAL REVISIONS NOT PERMITTED		TED		NONE		2/25/00		2/29/00	NO. A	I OF I	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for CCFL Fluorescent Lamps category:

Click to view products by JKL manufacturer:

Other Similar products are found below:

BF20170-38B BF4142-20B BF20137-26B BF2698-20B CF20228-31B CF26349-28B BF22140-24B BF22180-28B BF26180-24B BF5118-20B BF20125-28B BF20325-24B BF26214-20B BF26230-24B BF26240-24B BF26250-24B BF2661-24B BF386-20B BF20218-24B BF20226-24B BF20292-24B BF22258-25B BF22312-45B BF26318-20B BF3100-20B BF3228-21B BF5165-20B CF20305-24B BF3300-20B BF350-20B