

JKL LAMP PART NUMBER	COLOR RGB WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS) AVERAGE 20,000 MIN. 40,000 AVG.	
CF20228-31B	x = 0.276 y = 0.291	1300 @ 0°C	515	5	46,000 TYP.		
			500	7	50,000 TYP.	20,000 AVG.	

^{*} RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

MEASURING CONDITIONS: AMBIENT @25° \pm 1°, 45-85% RH, CALM CONDITIONS.

			METRIC	IN MILL	IONS ARE IMETERS ICE UNLESS	e		L COMPO	NENT	S COR	PORAT	TION
			THIRD ANGLE PROJECTION	1 PL + 2 PL + ANGLE +		TITLE	IVIIIVI	ATURE COL PRESCENT		HODE		
Α	REVISE ELECTRICAL		DRAWN BY L. WENGSTROM	APPV'D BY	7 DATE 3/23/05	SIZE A	55335	1.10	F202	28-31E	3	
REV. NO.	RELEASE & CANCEL P-0306-28 DESCRIPTION/ECO NUMBER	8/1/03 APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE	NONE	RELEASED DATE 11/3/03	REVISIOI DATE	3/23/05	NO. A	1 OF 1	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for CCFL Fluorescent Lamps category:

Click to view products by JKL manufacturer:

Other Similar products are found below:

BF20170-38B BF4142-20B BF20137-26B BF2698-20B CF20228-31B CF26349-28B BF22140-24B BF22180-28B BF26180-24B BF5118-20B BF20125-28B BF20325-24B BF26214-20B BF26230-24B BF26240-24B BF26250-24B BF2661-24B BF386-20B BF20218-24B BF20226-24B BF20292-24B BF22258-25B BF22312-45B BF26318-20B BF3100-20B BF3228-21B BF5165-20B CF20305-24B BF3300-20B BF350-20B